

D. Surfacing material will consist of native caliche. If required, road across pad will be surfaced with a minimum of 6" of caliche. Caliche will be obtained from the nearest BLM approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor.

3. Location of Existing Wells:

Exhibit "C" shows all existing wells within a one mile radius of proposed well. A list of these wells is shown on the attachment to Exhibit "C".

4. Location of Existing and/or Proposed Facilities:

In the event the proposed well proves to be productive, Strata Production Company will furnish maps or plats showing On Well pad facilities and Off Well pad facilities (if needed) by Sundry Notice before construction of these facilities starts.

5. Location and Type of Water Supply:

The well will be drilled with a combination of brine and fresh water mud systems as outlined in the Hole Prognosis. The water will be purchased from commercial water stations in the area and trucked to the location by transport over the existing and proposed access roads shown in Exhibit "B". If a commercial fresh water source is nearby, fasline may be laid along existing road ROW's and fresh water pumped to the well. No water well will be drilled on the location.

6. Source of Construction Materials:

All caliche required for construction of the drill pad and the proposed new access road (approximately 2500 cubic yards) will be obtained from a BLM approved caliche pit. All roads and pads will be constructed of 6" rolled and compacted caliche.