

## AUXILIARY EQUIPMENT

**DRAWWORKS** BDW 650M 650 HP, with Parmac Hydromatic brake

**ENGINES** Two Caterpillar D-353 diesels rated at 425 HP each

**ROTARY** Ideco 23", 300 ton capacity

**MAST/SUB** Ideal 132', 550,000 lb rated static hook load with 10 line  
Wagner 15' high substructure

**TRAVELLING  
EQUIPMENT** Gardner-Denver, 300 ton, 5 sheave w/ BJ 250 ton hook.  
Brewster Model 7 SX 300 ton swivel.

**PUMPS** Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound  
driven.

**PIT SYSTEM** 1-Shale Pit 6X7X35', 1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/ 5 mud  
agitators. Two centrifugal mud mixing pumps and a Double Screen Shale  
Shaker.

**LIGHT  
PLANT** Two CAT 3306 diesel electric sets 180 KW prime power.

**BOP  
EQUIP** 13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular  
Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon  
closing unit.

Exhibit D  
Santa Fe Energy Operating Partners, L.P.  
Sterling Silver "33" Federal No. 8  
Section 33, T-23S, R-31E  
Eddy County, New Mexico

DDR/tjm  
SS338