Form 3160-5 (June 1990)	DEPARTM	TED STATES T OF THE INTERIOR LAND MANAGEMENT	1 S. 1st Street	
BUREAU OF LAND MANAGEMENT 1 S. 1st Stream SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals				5. Lease Designation and Serial No. NM-NM0404441 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE				N/A
1. Type of Well Oit Gas Well Other				7. If Unit or CA, Agreement Designation
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA)				8. Well Name and No.
 Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 				Barclay "11G" Federal #7 9. API Well No. 30-015-27622
 Location of Well (Footage. Sec., T., R., M., or Survey Description) 1980' FEL & 1980' FNL Unit G Section 11-T23S-R31E 				 10. Field and Pool, or Exploratory Area Ingle Wells (Delaware) 11. County or Parish, State Eddy County, New Mexico
CHECK APPI				
	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORTING TYPE OF SUBMISSION TYPE OF ACTION			
 Notice of Intent Subsequent Report 		Abandonment Recompletion Plugging Back		Change of Plans Change of Plans New Construction Non-Routine Fracturing
Final Abandonment Notice	e	Casing Repair Altering Casing Nother Added perfs a	nd stimulated	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
04-09-98 thru 04 tubing. Ran bit a Perf'd MBC "E " Acidized with 10 packer. Frac'd w with 3930 psi. IS Cleaned out sand Ran 212 jts 2 7/8 04-28-98 thru 04-	-18-98 RU pulling nd scraper. Set RF 7510-7460' with 00 gals 7 ½% NeF ith 16,700 gals 30# SIP 3300 psi. with foam unit to "tubing, SN set at -30-98 RU pulling tubing and pump.	BP at 7750', press tested, spe 18 holes (.40" EHD). Set p e acid + 40 BS at AIR 63 B # X-link gel + 60,000# 16/3 7750'. TOH with RBP. Cl 7031'. Ran pump and rods. g unit. Pump was stuck. Re	rods. NU BOP. T otted 2 sx sand on t packer at 7430'. PM with 3000 psi. 0 Ottawa sd + 20,0 leaned out sand to 3 leaned out sand to 3 le	ISIP 275 psi. TOH with 00# RC sd at AIR 40.1 BPM 8356'. Circ'd hole clean. ing.
Title 18 U.S.C. Section 1001, makes to any matter within its jurisdiction.	it a crime for any person knowi	ngly and willfully to make to any department of	agency of the United States any	y false, fictitious or fraudulent statements or representatio
		*See Instruction on Rev	verse Side	