



DATE: 3/1/95

AMENDED: YES NO

L 1SE: Quabada Ridge 31 Feb 1
LUC: Sec 31-T22S-R29E
COUNTY: Eddy
STATE: New Mexico

13 3/8 54.5# K-55

SURFACE CSG SET @ 375

IN _____ HOLE

CMT TO SURFACE W/ 475 SX

8 5/8, 24# J-55 set @ 2714'
cmnt to surface w/ 875 shs

TOC 2200'

Prod. Tbg.

1. — jts 2 7/8 tbg to surface
2. Tubing anchor 5613' ±
3. 5 jts 2 7/8 tbg
4. 4' perf'd sub 5768
5. 1.25" ss N e 5772'
6. 29' mud Anchor 5773
7. ROT 5802

Squeeze Delaware 6104-6134 w/
1000 gals perma block + 1500 sx cmnt
Delaware 6104-6134 60 holes

cmnt net e 6195' squeeze w/
1500 gals perma block + 2500 sx cmnt

Delaware 6205-6215 20 holes
6215-6236 46 holes

Delaware 6248-6310 124 holes

TD _____ PSTD _____

cut window
6060-6090'
KOP 6065'

5 1/2 " 15.5# J-55 L765

CSG. SET @ 6500'

IN _____ HOLE

CMT W/ 915 SX