

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED

c19F

(See other instructions on reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL:		OIL WELL ☒	GAS WELL ☐	DRY ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF RESVR ☐
2. NAME OF OPERATOR DEVON ENERGY CORPORATION (NEVADA)						
3. ADDRESS AND TELEPHONE NO. 20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611						
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1980' FNL & 990' FEL Unit H Section 24-T23S-R31E At top prod. interval reported below (SAME) At total depth (SAME)						
15. DATE SPUDDED 12/2/96		16. DATE T.D. REACHED 12/21/96		17. DATE COMPL. (Ready to prod.) 1/26/97		18. ELEVATIONS (DF, FAS, RT, GR, ETC.)* GL 3555'
20. TOTAL DEPTH, MD & TVD 8706'		21. PLUG, BACK T.D., MD & TVD 8630'		22. IF MULTIPLE COMPL., HOW MANY? N/A		23. INTERVALS DRILLED BY →
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* Delaware 7065-8372'						25. WAS DIRECTIONAL SURVEY MADE NO
26. TYPE ELECTRIC AND OTHER LOGS RUN DLL/MLL/GR and ZDL/CN/GR and VDL/GR/CCL						27. WAS WELL CORED NO
28. CASING RECORD (Report all strings set in well)						
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD
13 3/8" H-40		48#		888'	17 1/2"	surf; 500 sx Poz C + 200 sx Cl C
8 5/8" J-55		32#		4401'	11"	surf; 1300 sx Poz C + 200 sx Cl C
5 1/2" J-55		15.5# & 17#		8705'	7 7/8"	3500'; 650 sx Cl H + 320 sx Cl C
				DV tool @ 5522'		
29. LINER RECORD						
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	30. TUBING RECORD	
					SIZE	DEPTH SET (MD)
					2 7/8"	7893'
31. PERFORATION RECORD (Interval, size and number)				32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
7065-7082' w/18 holes (.40" EHD) UBC "E"				DEPTH INTERVAL (MD)		
7102-7112' w/11 holes (.40" EHD) UBC "E"				AMOUNT AND KIND OF MATERIAL USED		
7130-7134' w/5 holes (.40" EHD) UBC "D"				7065-7134'		
7950-7965' w/16 holes (.40" EHD) MBC "B"				3000 gals 7 1/2% NeFe acid + 70 BS		
8176-8184' w/3 holes (.40" EHD) LBC "E"				35,500 gals 30# X-link gel + 147,000# 16/30 Ottawa sd +		
8131-8154' w/6 holes (.40" EHD) LBC "F"				33,000# 16/30 RC sd		
8215-8255' w/7 holes (.40" EHD) LBC "D"				(Continued on reverse)		
8320-8342' w/5 holes (.40" EHD) LBC "B"						
8368' & 8372' w/2 holes (.40" EHD) LBC "A"						
33.* PRODUCTION						
DATE FIRST PRODUCTION 2/6/97		PRODUCTIONS METHOD (Flowing, gas lift, pumping—size and type of pump) pumping				WELL STATUS (Producing or shut-in) producing
DATE OF TEST 2/7/97	HOURS TESTED 24	CHOKE SIZE	PROD'N FOR TEST PERIOD →	OIL-BBL. 119	GAS-MCF. 100	WATER-BBL. 328
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL-BBL. 119	GAS-MCF. 100	WATER-BBL. 328	OIL GRAVITY-API (CORR.) 38.6°
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) sold						
35. LIST OF ATTACHMENTS open hole logs, bond log, deviation survey report						
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records						

SIGNED Candace R. Graham

CANDACE R. GRAHAM
TITLE ENGINEERING TECHNICIAN

DATE February 28, 1997

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof: cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. (continued from the front)
		7950-7965'	2000 gals 7 1/2% NeFe acid (no BS used)
			19,000 gals 30# X-link gel + 51,000# 16/30 Ottawa sd + 9000# 16/30 RC sd
		8130-8372'	2500 gals 7 1/2% NeFe acid + 50 BS
			38,400 gals 30# X-link gel + 150,000# 16/30 Ottawa sd + 44,000# 16/30 RC sd

38.

GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	934'	
Salado	1265'	
Delaware	4538'	
Cherry Canyon	5476'	
Bone Spring	8430'	