

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

N.M. Oil Cons. Division

811 S. 1st Street
Artesia, NM 88210

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 1980' FEL Unit B Section 25-T23S-R31E

5. Lease Designation and Serial No.

NM0544986

6. Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Todd "25B" Federal #2

9. API Well No.

30-015-27705

10. Field and Pool, or Exploratory Area

Ingle Wells (Delaware)

11. County or Parish, State

Eddy Cnty, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

ACCEPTED FOR RECORD

DEC 11 1996

BLM

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud, csg string, TD

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well spud on 10-23-96 at 1045 hrs and drld a 17 1/2" hole to 887'. On 10-24-96 ran 19 jts 13 3/8" 48# H-40 ST&C csg, set at 887'; cemented w/500 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 11" hole to 4391'. On 10-31-96 ran 111 jts 8 5/8" 32# J-55 ST&C csg, set at 4390'; cemented w/1090 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 7 7/8" hole and reached TD 8628' at 0630 hrs 11-10-96. Western-Atlas ran DLL/MLL/GR and ZDL/CN/GR logs.

On 11-10-96 ran 204 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8627' w/DV tool at 5483'; cemented w/580 sx Class "H" + 320 sx Class "C"; preceded cement by 1000 gals sodium silicate preflush, TOC at 3500'.

Released rig at 1100 hrs 11-11-96. WOCU

14. I hereby certify that the foregoing is true and correct

Signed

Candace R. Graham

Title

CANDACE R. GRAHAM
ENGINEERING TECH.

Date 12/6/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: