

AUXILIARY EQUIPMENT

DRAWWORKS BDW 650M 650 HP, with Parmac Hydromatic brake

ENGINES Two Caterpillar D-353 diesels rated at 425 HP each

ROTARY Ideco 23", 300 ton capacity

MAST/SUB Ideal 132',550,000 lb rated static hook load with 10 line
Wagner 15' high substructure

TRAVELLING Gardner-Denver,300 ton,5 sheave w/ BJ 250 ton hook.
EQUIPMENT Brewster Model 7 SX 300 ton swivel.

PUMPS Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound driven.

PIT SYSTEM 1-Shale Pit 6X7X35',1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/ 5 mud agitators.
Two centrifugal mud mixing pumps and a Double Screen Shale Shaker.

LIGHT Two CAT 3306 diesel electric sets 180 KW prime power.
PLANT

BOP 13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular
EQUIP Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit.

Exhibit D
Santa Fe Energy Operating Partners,L.P.
Sterling Silver "33" Fed. No.6
Section 33, T-23S,R-31E
Eddy County, New Mexico

DDR:SS33-6.PMT