

ENERGEX COMPANY
TIRANO CNG STATE #1
660 FSL & 1980 FWL
SEC. 36-24S-28E
EDDY COUNTY, NEW MEXICO

RECEIVED

JUL 11 1994

O. C. D.
ARTESIA, OFFICE

SUNDRY NOTICE

5/6/94

Perforated 5244'-5248' w/2 spf and 6001'-6010' w/2 spf. Set RPB @ 6070' and tested to 2000#. Set packer @ 5956'. Acidized perfs 6001'-6010' w/ 500 gals 7 1/2% NeFe acid and 18 balls. Set RBP @ 5335' and test to 2000#. Set packer @ 5176'. Acidized perfs 5244'-5248 w/ 500 gals 7-1/2% NeFe acid and 4 balls. Set guiberson UNIVI @ 6070' and packer @ 5885'. Fraced perfs 6001'-6010' Via 2-7/8" tubing with 6,000 gals w/35# X/L gell and 10,100# 16/30 resin coated Ottawa sand.

5/11/94

Perforated 4894-4997' w/2 jspf. Sand Frac w/ 16,000 gals X/L gell and 15,000 20/40 ottawa followed by 15,000# 16/30 resin coated sand.

5/14/94

Squeezed perfs 4984'-4997' w/50 sxs class "C" + 1/2 pps ground walnut shells and 100 sxs class "C" to 2000# with 115 sxs in formation.

5/16/94

Perforated 4817'-4822' w/2 spf. Perf 4900'-4910' w/2 spf. 120 degree phasing. Acidized 4817'-4822' w/400 gals NeFe acid. Acidized 4900'-4910' 400# gals NeFe acid. Fraced 4900'-4910' and 4817'-4822' w/577 bbls X/L and 38,000# 20/40 sand.

5/20/94

Perforated 4620-4633' w/25 shots. Acidized w/750 gals. 7-1/2% NeFe acid.. Fraced w/40,000# RC sand @ 5-6 BPM. Put well on pump.

6/8/94

Set PKR @ 4725' to seal off perfs 4620-4633'.