## Form: 3160-5 (June 1990)

## UNITED STATES DEPARTMEL OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NM OIL CONS COMMISSION Drawer DD

5. Lease Designation and Serial No.

Artesia, NM 88210

**FORM APPROVED** Budget Bureau No. 1004-0135 Expires March 31, 1993

CIST
------

W BUILDE NOTICE	AND REPORTS ON WELLS	5. Lease Designation and Serial No.			
Do not use this form for proposals to drill o	or to deepen or reentry to a different reservoir.	040441			
Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name			
477		NA I			
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation			
1. Type of Well		_ / 2 0.20 11 01.1 12 01.2			
⊠ Oil ☐ Gas ☐ Other Well		NA			
2. Name of Operator		8. Well Name and No.			
DEVON ENERGY CORPORATION (NEVA	DA)	Todd "13K" Federal #11			
3. Address and Telephone No.		9. API Well No.			
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4511		30-015-27859			
		10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)		ingle Wells (Delaware)			
Sec 13-T23S-R31E 2180' FWL & 1920' FSL		11. County or Parish, State			
	UNITE	]			
		Eddy County, NM			
CHECK APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA			
TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent	Abandonment	Change of Plans			
_	Recompletion	New Construction			
Subsequent Report	Plugging Back	Non-Routine Fracturing Water Shut-Off			
	Casing Repair	Conversion to Injection			
Final Abandonment Notice	☐ Altering Casing ☐ Other spud, set surface, intermediate, prod csg	Dispose Water			
	Other sputt, set surface, intermediate, prod esg	(Note: Report results of multiple completion on Well			
	A death and the continue dates including estimated date of starting any n	Completion or Recompletion Report and Log form.)			
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*					
locations and measured and true vertical depths for all market	s das some perdentition of the manny	locations and measured and the various depairs of an initial to the parties of th			
locations and measured and true vertical depths for all market					
docations and measured and true vertical depths for all market 4/10/95 Spudded well at 8:00 a.m.	· ·				
4/10/95 Spudded well at 8:00 a.m.					
4/10/95 Spudded well at 8:00 a.m. 4/12/95 Ran 19 ints 13 3/8" 48# H-40	8rd surface casing w/ the guide shoe @ 854' and the	ne float collar @ 766'. The casing was			
4/10/95 Spudded well at 8:00 a.m. 4/12/95 Ran 19 ints 13 3/8" 48# H-40	8rd surface casing w/ the guide shoe @ 854' and the	ne float collar @ 766'. The casing was a CC + 1/2 #/sx CF (14.8 ppg, 1.32 cu			
4/10/95 Spudded well at 8:00 a.m. 4/12/95 Ran 19 ints 13 3/8" 48# H-40	8rd surface casing w/ the guide shoe @ 854' and the	ne float collar @ 766'. The casing was CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu			
4/10/95 Spudded well at 8:00 a.m. 4/12/95 Ran 19 ints 13 3/8" 48# H-40		the float collar @ 766'. The casing was $CC + \frac{1}{4} \#/\text{sx } CF \text{ (14.8 ppg, 1.32 cu})$			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci	8rd surface casing w/ the guide shoe @ 854' and the l2.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" + 22 rc'd to surface.	CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 S	8rd surface casing w/ the guide shoe @ 854' and the l2.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" 22/2 rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' and the guide sh	A CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu C = 1 V = 1 D pd the float collar @ 4263'. The			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 Scasing was cemented with 1300 sx Lite + 1	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" + 29/20 rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx)	CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu c			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 S	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" + 29/20 rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx)	CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu c			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/ sx). Circulated 125	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "G" + 22/crc'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' a 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/ sx). Circulated 125	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "G" + 22/crc'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' a 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx ci  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/ sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 175	8rd surface casing w/ the guide shoe @ 854' and the later page 1.93 cu ft/sx) and 200 sx class "C" + 22/2 re'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  © [ ]	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 175 @ 5304'. The 1st stage was cemented w/ 75	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" 22/27 rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' at 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 1)	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC  CON DIV  The float collar @ 8603' & DV tool  .74 cu ft/sx). 92 sx circ'd above DV			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304". The 1st stage was cemented w/ 72 tool. 5/2/95 Cmtd 2nd stage: 350 sx 65:35	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "G" + 22/rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' a 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' a 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 155 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC  CON DIV  The float collar @ 8603' & DV tool  .74 cu ft/sx). 92 sx circ'd above DV			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/ sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304". The 1st stage was cemented w/ 70 tool. 5/2/95 Cmtd 2nd stage: 350 sx 65:35 followed w/ 250 sx class "C" w/ 4% gel + 6	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" 22/27 rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' at 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 1)	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC  CON DIV  The float collar @ 8603' & DV tool  .74 cu ft/sx). 92 sx circ'd above DV			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304". The 1st stage was cemented w/ 72 tool. 5/2/95 Cmtd 2nd stage: 350 sx 65:35	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "G" + 22/rc'd to surface.  TC intermediate csg w/ the guide shoe @ 4349' a 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' a 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 155 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC  CON DIV  The float collar @ 8603' & DV tool  .74 cu ft/sx). 92 sx circ'd above DV			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304'. The 1st stage was cemented w/ 250 sx class "C" w/ 4% gel + 14. Thereby certify that the foregoing is true and correct	8rd surface casing w/ the guide shoe @ 854' and the large shoe good sections and 200 sx class "C" + 22/2 re'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  For J-55 LT&C prod csg w/ the float shoe @ 8650' at 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 15 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce 15.5% salt + ½ #/sx CF (13.6 ppg, 1.75 cu ft/sx).  Charles W. Horsman	a CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu and the float collar @ 4263'. The yield) and 200 sx class "C" w/ 2% CC CON DIVI and the float collar @ 8603' & DV tool .74 cu ft/sx). 92 sx circ'd above DV llo seal (12.7 ppg, 1.95 cu ft/ sx)			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304'. The 1st stage was cemented w/ 250 sx class "C" w/ 4% gel + 10 (14.1 hereby certify that the foregoing is true and correct Signed	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" + 22/2 rc'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' at 200 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 155 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce 6.5% salt + ½ #/sx CF (13.6 ppg, 1.75 cu ft/sx).	nd the float collar @ 4263'. The yield and 200 sx class "C" w/ 2% CC  CON DIV  The float collar @ 8603' & DV tool  .74 cu ft/sx). 92 sx circ'd above DV			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304'. The 1st stage was cemented w/ 250 sx class "C" w/ 4% gel + 14. Thereby certify that the foregoing is true and correct	8rd surface casing w/ the guide shoe @ 854' and the large shoe good sections and 200 sx class "C" + 22/2 re'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  For J-55 LT&C prod csg w/ the float shoe @ 8650' at 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 15 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce 15.5% salt + ½ #/sx CF (13.6 ppg, 1.75 cu ft/sx).  Charles W. Horsman	a CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu and the float collar @ 4263'. The yield) and 200 sx class "C" w/ 2% CC CON DIVI and the float collar @ 8603' & DV tool .74 cu ft/sx). 92 sx circ'd above DV llo seal (12.7 ppg, 1.95 cu ft/ sx)			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/ sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304'. The 1st stage was cemented w/ 7 (2) tool. 5/2/95 Cmtd 2nd stage: 350 sx 65:33 followed w/ 250 sx class "C" w/ 4% gel + 14. I hereby certify that the foregoing is true and correct Signed (This space for Federal or State office use)	8rd surface casing w/ the guide shoe @ 854' and the large shoe good sections and 200 sx class "C" + 22/2 re'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  For J-55 LT&C prod csg w/ the float shoe @ 8650' at 100 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 15 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce 15.5% salt + ½ #/sx CF (13.6 ppg, 1.75 cu ft/sx).  Charles W. Horsman	a CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu and the float collar @ 4263'. The yield) and 200 sx class "C" w/ 2% CC CON DIVI and the float collar @ 8603' & DV tool .74 cu ft/sx). 92 sx circ'd above DV llo seal (12.7 ppg, 1.95 cu ft/ sx)			
4/10/95 Spudded well at 8:00 a.m.  4/12/95 Ran 19 jnts 13 3/8" 48# H-40 cemented with 500 sx Lite + 1/4 #/sx CF (ft/sx) displaced w/ 10 ppg brine. 150 sx cit  4/19/95 Ran 107 jnts 8 5/8" 32# J-55 St casing was cemented with 1300 sx Lite + 1 (14.8 ppg, 1.32 cu ft/sx). Circulated 125  5/1/95 Ran 200 jnts 5½", 15.5" & 17:0 (2) 5304'. The 1st stage was cemented w/ 250 sx class "C" w/ 4% gel + 10 (14.1 hereby certify that the foregoing is true and correct Signed	8rd surface casing w/ the guide shoe @ 854' and the 12.7 ppg, 1.93 cu ft/sx) and 200 sx class "C" ± 22/2 rc'd to surface.  STC intermediate csg w/ the guide shoe @ 4349' at 5#/sx NaCl + ½ #/sx CF (12.7 ppg, 2.21 cu ft/sx sx cmt.  # J-55 LT&C prod csg w/ the float shoe @ 8650' at 200 sx "H" + 8#/sx CSE & ½ #/sx CF (13.6 ppg, 155 Lite "C" w/ 4% Claystay + 10% salt + ½ #/sx ce 6.5% salt + ½ #/sx CF (13.6 ppg, 1.75 cu ft/sx).  Charles W. Horsman  Title District Engineer	a CC + 1/4 #/sx CF (14.8 ppg, 1.32 cu  Ind the float collar @ 4263'. The  yield and 200 sx class "C" w/ 2% CC  CON DIVINA  Date 5/15/95			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States arry false, fictitious or fraudulent statements or representations as to