

CSF

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

OCT 11 1994

2. Name of Operator
Devon Energy Corporation (Nevada)

O. C. D.
ARTESIA, OFFICE

3. Address and Telephone No.
20 N. Broadway Suite 1500 Oklahoma City, OK 73102

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980 FSL & 330 FWL
510
35 miles west-northwest of Jal, NM

27-235-31E

FORM APPROVED
Budget Bureau No 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No
NM 0418220-A

6. If Indian, Allottee or Tribe Name
NA

7. If Unit or CA, Agreement Designation
NA

8. Well Name and No.
TODD "27L" A Federal #12

9. API Well No.

10. Field and Pool, or Exploratory Area
Ingle Wells Delaware

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other set surface casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 8/25/94, we ran 13 3/8" casing as follows: Shoe @ 865', Float Collar @ 773', 6 centralizers at 825', 635', 452', 270', 87', & 41', 19 jts of 13 3/8", 48 ppf, H-40, 8rd STC csg. The casing was cemented as follows by Dowell Schlumberger:

450 sxs 35/65 POZ C + 6% gel + 2% CaCl and 1/4#/sx celloflake.
200 sxs C + 2% CaCl and 1/4#/sx celloflake.

We circulated 58 sx cement to surface.

14. I hereby certify that the foregoing is true and correct

Signed Linda Pieperbrock Title Engineering Technician

Date 8/30/94

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side