

COCHITI "5" FEDERAL #1  
API #30-015-27996

FORM 3160-4 WELL COMPLETION OR RECOMPLETION REPORT AND LOG

ITEM 32: ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC:

<u>DEPTH INTERVAL</u>	<u>AMOUNT AND KIND OF MATERIAL USED</u>
9784'	SPOTTED 50 SXS CEMENT UP TO 9554'
9180'	SET CIBP & CAPPED W/35' CEMENT.
6571'	SPOTTED 350 GALS 7-1/2% MUD CLEAN OUT, TRIPLE-INHIBITED ACID, & TREATED PERFS W/1500 GALS 7-1/2% MUD CLEAN OUT ACID
6514 - 6571'	FRAC'D PERFS W/34,000 GALS 35# X-LINKED GEL CARRYING 103,500# 16/30 MESH OTTAWA SAND + 19,000# 16/30 RESIN-COATED SAND

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

RECEIVED

AUG 26 1961

BLM  
ROSWELL, NM