

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or to enter to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-81952

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Llama ALL Federal #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Wildcat Morrow

11. County or Parish, State

Eddy Co., NM

Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

Address and Telephone No.

105 South 4th St., Artesia, NM 88210

Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 950' FWL of Section 7-T22S-R31E (Unit M, SWSW)

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 17-1/2" hole with rotary tools at 4:00 AM 9-3-94. NOTE: Notified Leta w/BLM Answering Service prior to resuming drilling.

TD 650'. Reached TD at 2:30 PM 9-3-94. Ran 15 joints of 13-3/8" 48# H-40 (664.42') of casing set at 650'. 1-Texas Pattern notched guide shoe set at 650'. Insert float set at 604.91'. Cemented with 450 sacks Pacesetter Lite, 1/4#/sack celloseal and 2% CaCl2 (yield 1.01, weight 12.4). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 PM 9-3-94. Bumped plug to 500 psi, float did not hold. Circulated 215 sacks. WOC. Drilled out at 10:30 AM 9-5-94. WOC 37 hours. Nipped up and tested to 1500# for 30 minutes. Reduced hole to 12-1/4". Resumed drilling. NOTE: Preceded cement with 20 bbls water. Centralizers on joints 1, 3 & 5. Notified Leta with BLM Answering Service prior to cementing.

14. I hereby certify that the foregoing is true and correct

Signed Kusty Klein

Title Production Clerk

Date Sept. 8, 1994

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side