CONDITIONS OF APPROVAL, IF ANY:

Y OIL CONS COMMISSION

c15F

		Lamer Dn	
orm 3160-5 UNI	TED STATES	Artesia, NM 88210 FORM APPROVED	
5dile 1999)	NT OF THE INTERIOR	Budget Bureau No. 1004-0135	
BUREAU OF	LAND MANAGEMENT	Expires: March 31, 1993	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		5. Lease Designation and Serial No. NM-29233	
, ,	OR PERMIT" for such proposals	6. If Indian, Alottee or Tribe Name	
		7. If Unit or CA, Agreement Designation	
SUBM	IT IN TRIPLICATE		
1. Type of Well: OIL GAS OTHER		8. Well Name and Number NEFF '13' FEDERAL	
2. Name of Operator TEXACO EXPLORA	ATION & PRODUCTION INC.	9	
B. Address and Telephone No. P.O. Box 46510, De	enver Colorado 80201-6510 (303)621-485	9. API Well No. 30-015-28125	
 Location of Well (Footage, Sec., T., R., M., or Survey Unit Letter C: 660 Feet From Th 	Description) ne NORTH Line and 1980 Feet From The	10. Field and Pool, Exploratory Area LIVINGSTON RIDGE DELAWARE	
Office Letter Co. 1 Co.	Tect form the	11. County or Parish, State	
WEST Line Section 13	Township <u>22-S</u> Range <u>31-E</u>	EDDY , NM	
2. Check Appropriate	Box(s) To Indicate Nature of Notice, Re	eport, or Other Data	
TYPE OF SUBMISSION	Т	YPE OF ACTION	
	Abandonment	Change of Plans	
Notice of Intent	Recompletion	New Construction	
	☐ Plugging Back	Non-Routine Fracturing	
Subsequent Report	Casing Repair	Water Shut-Off Conversion to Injection	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
i		1 CSG Dispose Water (Note: Report results of multiple completion on Well	
	į.	Completion or Recompletion Report and Log Form)	
 RAN 21 JOINTS OF 11.75, 42#, WC-40, ST DOWELL CEMENTED WITH 575 SACKS OF CIRCULATED 127 SACKS. NU BOP & TESTED TO 1200#. TESTED C. WOC TIME 12.5 HOURS FROM 3:00 AM 1 DRILLING 11 INCH HOLE. DRILLED 11 INCH HOLE TO 4393'. TD @ 8 RAN 102 JOINTS OF 8 5/8, 32# K-55 STC 0 DOWELL CEMENTED W/ 1000 SACKS 35. SACKS CLASS H W/ 1% CACL2 (15.6 PP0 	3:00 PM 12-14-94. CASING SET @ 4393'. RAN 3 CENTRALIZERS. /65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCE G, 1.18 CF/S). PLUG DOWN @ 8:30 PM 12-14-94. CIR D CASING TO 1200# FOR 30 MINUTES FROM 5:00 AI	DOWN @ 3:00 AM 12-09-94. O 3:30 PM 12-09-94. ELE (12.8 PPG, 1.94 CF/S). F/B 200 CULATED 203 SACKS	
14 hereby certify that the foregoing is true and correct SIGNATURE C.P. Boshem	SI⊵∰ ⊺ITLE Drilling Operations Mgr.	SJS DATE 12-20-94	
TYPE OR PRINT NAME C. P. B			
(This space for Federal or State office use) APPROVED BY	TITLE	DATE	