

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL CONS COMMISSION
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

APR 13 11 07 AM '95

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
NM-85893

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cedar Canyon 21 Fed. #1

9. API Well No.

30-015-28354

10. Field and Pool, or Exploratory Area

Cedar Canyon Delaware

11. County or Parish, State

Eddy County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 330' FEL, Section 21, T24S, R29E

MAY 15 1995

CONFIDENTIAL

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set Surface Csg
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU Nabors #301. Spud @ 1330 hrs CST 02/21/95. Drilled 11" hole to 580'. TD reached 2245 hrs CST 02/21/95. Ran 13 jts 8-5/8" 24# J-55 ST&C casing. TPGS @ 580'. IFV @ 534'. Howco cmt'd casing w/ 250 sxs Halliburton Lite @ 12.7 ppg followed by 200 sxs Class "C" + 2% CaCl₂ @ 14.8 ppg. Plug down @ 0230 hrs CST 02/21/95. Recovered 96 sx excess cement. WOC 13 hrs. Cement has a compressive strength over 500 psi after 8 hours. Make cut-off. Weld on wellhead and test to 500 psi. NU BOP's and test to 1000 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title Senior Operations Engineer

Date April 10, 1995

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO