

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-28401

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil / Gas Lea

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐
b. Type of Completion:
NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator
P.O. BOX 730, HOBBS, NM 88240

4. Well Location
Unit Letter K : 1980 Feet From The SOUTH Line and 1980 Feet From The WEST Line
Section 30 Township 23-S Range 30-E N1MPM EDDY COUNTY

10. Date Spudded
6/26/95
11. Date T.D. Reached
7/11/95
12. Date Compl. (Ready to Prod.)
7/31/95
13. Elevations DF & RKB, RT, GR, etc.)
3074'
14. Elev. Csghead

15. Total Depth
8500'
16. Plug Back T.D.
8453'
17. If Mult. Compl. How Many Zones
18. Intervals Drilled By
19. Producing Intervals, of this completion - Top, Bottom, Name
8240-8262; 7904-7938; 7167-7204; 8207-8338; 6893-6926
20. Was Directional Survey Made
NO
21. Type Electric and Other Logs Run
AIT-LDT-CNL-NGT-GR; GR-WLTD; GR-CCL
22. Was Well Cored
YES

CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOSE SIZE	CEMENT RECORD	AMOUNT PULLED
11-3/4"	42#	410'	14-3/4"	250 SACKS	
8-5/8"	24#	3220'	11"	850 SACKS	
5-1/2"	15.5, 17#	8500'	7-7/8"	1650 SACKS	

LINER RECORD					TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
NONE					2-7/8"	6844'	

26. Perforation record (interval, size, and number)
8207-8338, SQZD
8240-8262', 2 JSPF, 44 HOLES, SQZD
7904-7938, 2 JSPF, 64 HOLES, SQZD
7167-7204, 2JSPF, 54 HOLES, SQZD
6893-6926
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
DEPTH INTERVAL
6893-6926
AMOUNT AND KIND MATERIAL USED
1700g 7.5% F7200g 30#25000#1630

28. PRODUCTION
Date First Production
8/1/95
Production Method (Flowing, gas lift, pumping - size and type pump)
(2-1/2" X 1-3/4" X 25") PUMP
Well Status (Prod. or Shut-in)
PROD
Date of Test
1/15/96
Hours tested
24
Choke Size
48/64"
Prod'n For Test Period
Oil - Bbl.
22
Gas - MC
44
Water - Bbl.
245
Gas - Oil Ratio
2000
Flow Tubing Press.
75#
Casing Pressure
600#
Calculated 24-Hour Rate
Oil - Bbl.
Gas - MCF
Water - Bbl.
Oil Gravity - API -(Corr.)
42.9

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
WAITING ON CONNECTION
Test Witnessed By
KEL/DBS

30. List Attachment
DEVIATION SURVEY

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.
SIGNATURE M. Angie Davila TITLE Clerk DATE 2/28/96
TYPE OR PRINT NAME M. Angie Davila Telephone No. 397-0443

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	3215'	T. Canyon	
T. Salt		T. Strawn	
B. Salt	3316'	T. Atoka	
T. Yates		T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen		T. Silurian	
T. Grayburg		T. Montoya	
T. San Andres		T. Simpson	
T. Glorieta		T. McKee	
T. Paddock		T. Ellenburger	
T. Blinebry		T. Gr. Wash	
T. Tubb		T. Delaware Sand	3346'
T. Drinkard		T. Bone Springs	7056'
T. Abo		T.	1ST BS 8098'
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 6893 to 6926
No. 2, from to

No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	3215'	3215'	ANHY, DOLO				
3215'	3316'	101'	DOLO, LIMESTONE, SHALE				
3316'	3346'	30'	DOLO, LIMESTONE				
3346'	3432'	86'	SAND				
3432'	4100'	668'	LI, SD, SHALE				
4100'	5400'	1300'	SAND				
5400'	6828'	1428'	SAND				
6828'	7056'	228'	LI, SD, SHALE				
7056'	8098'	1042'	LIME, SHALE				