

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28422

Operator <u>Texaco Expl + Prod</u>		Lease <u>Remuda Basin St</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>19</u>	Township <u>23</u>	Range <u>30</u>	County <u>Eddy</u>
Drilling Contractor <u>NA</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	* <u>11 3/4</u>	<u>42 #</u>	<u>Daylight only</u>	<u>400'</u>	<u>250 Surf</u>
<u>11</u>	* <u>8 5/8</u>	<u>34 #</u>		<u>3200'</u>	<u>850 Surf</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5 #</u>		<u>7500'</u>	<u>1650 Surf</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
 (Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 11" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 3190' Set 3190' Feet of 8 5/8" Inch 36 # Grade Wildcat - 40

(New) used csg. @ 3190' with 100-cl. H. sacks neat cement around shoe
 + 800 sack 35/65 per. H. additives 670 gel., 570 salt, 1/4" ccl.

Plug down @ 9:45 (AM) (PM) Date 3-9-96

Cement circulated yes No. of Sacks 162 sk

Cemented by Dowell Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Airpocket - 520'

11" hole R.T. 20 hours

B. Salt - 3065'