

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

811 S. 1st Street
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL Unit J Section 25-T23S-R31E

5. Lease Designation and Serial No.

NM0344986

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Todd "25J" Federal #10

9. API Well No.

30-015-28806

10. Field and Pool, or Exploratory Area

Ingle Wells (Delaware)

11. County or Parish, State

Eddy Cnty, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

ACCEPTED FOR RECORD

DEC 11 1996

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud, csg string, TD

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well spud on 11-12-96 at 1715 hrs and drld a 17 1/2" hole to 888'. On 11-14-96 ran 19 jts 13 3/8" 48# H-40 ST&C csg, set at 887'; cemented w/500 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 11" hole to 4361'. On 11-20-96 ran 98 jts 8 5/8" 32# J-55 ST&C csg, set at 4360'; cemented w/1050 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 7 7/8" hole and reached TD 8642' at 0600 hrs 11-30-96. Western-Atlas ran DLL/MLL/GR/C and ZDL/CN/GR/C logs.

On 12-01-96 ran 205 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8644' w/DV tool at 5519'; cemented w/590 sx Class "H" + 330 sx Class "C"; preceded cement by 1000 gals sodium silicate preflush; TOC at 3500'

Released rig at 0900 hrs 12-02-96. WOCU.

14. I hereby certify that the foregoing is true and correct

Signed Candace R. Graham

Title

CANDACE R. GRAHAM
ENGINEERING TECH.

Date 12/6/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: