

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Cons. Division  
811 S. 1st Street  
Albuquerque, NM 88210-2397

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 238-6611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 1980' FEL Unit O Section 25-T23S-R31E

5. Lease Designation and Serial No.

NM0544986

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Todd "250" Federal #15

9. API Well No.

30-015-28860

10. Field and Pool, or Exploratory Area

Ingle Wells (Delaware)

11. County or Parish, State

Eddy Cnty, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, casing strings, TD

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well spud on 02-04-97 at 1630 hrs and drld a 17 1/2" hole to 896'. On 02-05-97 ran 20 jts 13 3/8" 48# H-40 ST&C csg, set at 894'; cemented w/575 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 11" hole to 4426'. On 02-12-97 ran 105 jts 8 5/8" 32# J-55 ST&C and LT&C csg, set at 4425'; cemented w/1010 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 7 7/8" hole and reached TD 8671' at 1515 hrs 02-19-97. Schlumberger ran MSFL/DLL/GR and LDT/CNT/GR logs on 02-20-97.

On 02-22-97 ran 205 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8670' w/DV tool at 5523'; cemented w/510 sx Class "H" + 320 sx Class "C"; preceded cement by 1000 gals sodium silicate preflush; TOC at 3500'.

Released rig at 1200 hrs 02-21-97. WOCU.

14. I hereby certify that the foregoing is true and correct

Signed Candace R. Graham

CANDACE R. GRAHAM  
ENGINEERING TECH.

Date 2/27/97

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

ACC  
(ORIG. SGD.) DAVID R. GLASS

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side