

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT --" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other:

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1330' FNL and 990' FWL (SW NW) Unit E
Sec. 10, T24S-R26E

5. Lease Designation and Serial No.
LC-064200

6. If Indian, Allotee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Black River 10 Federal Comm. No. 1

9. Well API No.

30-015-29018

10. Field and Pool, or Exploratory Area

S. Carlsbad Morrow, Gas

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other: TD/Production Csg
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

8/19/96: Drill 12-1/4" hole to 3808'. Run CND/GR log. Ran 9-5/8" x 53.5# csg to 3807'. Cement with 1050 sks P/L + 1/4 lb. celloseal followed by 200 sks class C + 2% CaCl2. PD at 3:30 am
8/29/96. Circ 104 sks to surface.

8/29/96: Drill 7-7/8" hole to 11,862' (TD). Ran 5-1/2" x 23# csg to 11,858'. DV tool at 9493'. Cement 1st stage with 560 sks Super C Modified + 5# gilsonite + .44#/sx FL-52 + .44#/sx FL-25. Plug down at 9:22 am 10/7/96. Circulate 100 sks to surface. Cement 2nd stage with 675 sks P/L + .3% salt + 4/10% FL-52 + 1/4# celloseal followed by 100 sks H + 4/10% FL-52. Plug down at 6:40 pm 10/7/96. Cement top at 3808'.

14. I hereby certify that the foregoing is true and correct

Signed

Duane C. Winkler

Title

Production Superintendent

Date

10-9-96

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

Title

Date

Conditions of approval, if any:

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*See Instruction on Reverse Side