

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-29102

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
TODD "36B" STATE

8. Well No.
15

9. Pool name or Wildcat
Single Wells (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
DEVON ENERGY CORPORATION (NEVADA)

3. Address of Operator

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Well Location

Unit Letter B : 330 Feet From The NORTH Line and 2310 Feet From The EAST Line

Section 36 Township 23S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

GL 3511'

Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, csg string, TD ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

This well spud on 09-09-96 at 1800 hrs and drld a 17 1/2" hole to 882'. On 09-11-96 ran 19 jts 13 3/8" 48# H-40 ST&C csg, set at 882'; cemented w/500 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 11" hole to 4395'. On 09-18-96 ran 110 jts 8 5/8" 32# J-55 ST&C csg, set at 4394'; cemented w/1130 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.

Drld 7 7/8" hole and reached TD 8581' at 2345 hrs 09-26-96. Western-Atlas ran DLL/MLL/GR and ZDL/CN/GR logs.

On 09-28-96 ran 201 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8580' w/DV tool at 5510'; cemented w/790 sx Class "H" + 390 sx Class "C"; preceded cement by 1000 gals sodium silicate preflush; TOC at 3500'.

Released rig at 0300 hrs 09-29-96. WOCU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Candace R. Graham TITLE ENGINEERING TECHNICIAN

DATE October 2, 1996

TYPE OR PRINT NAME Candace R. Graham

TELEPHONE NO. (405) 235-3611

(This space for State ORIGINAL SIGNED BY TIM W. GUM

DISTRICT II SUPERVISOR

Approved by _____ TITLE _____

DATE OCT 15 1996

Conditions of approval, if any: