

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 no Brazos Rd, Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
**30-015-29292**

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
**K-952**

7. Lease Name or Unit Agreement Name  
**TODD "36G" STATE**

8. Well No.  
**8**

9. Pool name or Wildcat  
**Ingle Wells (Delaware)**

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
**DEVON ENERGY CORPORATION (NEVADA)**

3. Address of Operator  
**20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611**

4. Well Location  
Unit Letter **G** : **1980** Feet From The **NORTH** Line and **1980** Feet From The **EAST** Line

Section **36** Township **23S** Range **31E** NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
**GL 3517'**

Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Spud, csg string, TD ☒

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

**This well spud on 02-22-97 at 1600 hrs and drld a 17 1/2" hole to 851'. On 02-23-97 ran 19 jts 13 3/8" 48# H-40 ST&C csg, set at 850'; cemented w/480 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.**

**Drld 11" hole to 4416'. On 03-02-97 ran 105 jts 8 5/8" 32# J-55 ST&C csg, set at 4415'; cemented w/1000 sx 35/65 Pozmix "C" + 200 sx Class "C"; TOC at surface.**

**Drld 7 7/8" hole and reached TD 8636' at 1800 hrs 03-09-97. Schlumberger ran DLL/MSFL/GR and LDT/CNL/GR logs.**

**On 03-11-97 ran 209 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8635' w/DV tool at 5006'; cemented w/350 sx Class "H" (TOC calculated at 6708') + 410 sx Class "H" (TOC calculated at 5006') + 250 sx Class "C" (TOC calculated at 3500'); preceded cement by 1000 gals sodium silicate preflush.**

**Released rig at 1200 hrs 03-12-97. WOCU.**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Candace R. Graham

TITLE ENGINEERING TECHNICIAN

DATE March 20, 1997

TYPE OR PRINT NAME Candace R. Graham

TELEPHONE NO. (405) 235-3611

(This space for State use)

**ORIGINAL SIGNED BY TIM W. GUM**  
**DISTRICT II SUPERVISOR**

Approved by \_\_\_\_\_  
Conditions of approval, if any:

TITLE \_\_\_\_\_

DATE **MAR 28 1998**