

LOST Tank Delaware WEST 76582

Form 3160-3
(July 1992)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN THE CASE
(Other than on reverse side)

FORM APPROVED
OMB NO. 1004-0134
Expires: February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1A. TYPE OF WORK

DRILL ☒

DEEPEN ☐

B. TYPE OF WELL

OIL WELL ☒

GAS WELL ☐

OTHER ☐

SINGLE ZONE ☒

MULTIPLE ZONE ☐

2. NAME OF OPERATOR

POGO PRODUCING COMPANY/789/ (RICHARD WRIGHT)

3. ADDRESS AND TELEPHONE NO.

P.O. BOX 10340 MIDLAND, TEXAS 79702-7340 Ph. 915-682-6822

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

330' FNL & 990' FWL SEC. 3 T22S-R31E EDDY CO. NEW MEXICO

At proposed prod. zone Same

Unit D

LOT 4

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

Approximately 28 miles Southeast of Carlsbad New Mexico

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT.
(Also to nearest drilg. unit line, if any)

330'

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.

NA

19. PROPOSED DEPTH

8300' 8150' 8150'

17. NO. OF ACRES ASSIGNED TO THIS WELL

40

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3475' GR.

22. APPROX. DATE WORK WILL START*

As soon as approved

23.

PROPOSED CASING AND CEMENT

CARLSBAD-CONTROLLED WATER BASIN

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
26"	Conductor pipe	NA	40'	Cement to surface/Redi-Mix
17 1/2"	J-55 13 3/8"	54.5	650 550' 8150'	650 Sx. Circulate to surface
11"	J-55 8 5/8"	32# & 24#	4000'	1375 Sx. Circulate to surface
7 7/8"	J-55 5 1/2"	17# & 15.5#	8150 8300'	1975 Sx. Circulate to surface

SECRETARY'S POTASH

5-111-P POTASH

Cement in 3 Stages

1. Drill 26" hole to 40'. Set 40' of 20" conductor pipe and cement with Redi-Mix to surface. APPROVAL SUBJECT TO

2. Drill 17 1/2" hole to 550'. Run and set 550' of 13 3/8" 54.5# J-55 ST&C casing. Cement with 450 Sx. 35:65:6 POZ Class "C" Light cement + 2% CaCl, tail in with 200 Sx. Class "C" + 2% CaCl circulate cement to surface. GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED

3. Drill 11" hole to 4000'. Run and set 8 5/8" casing as follows: 1800' of 32# J-55 ST&C 1200' of 24# J-55 ST&C, 1000' of 32# J-55 ST&C casing. Cement with 1175 Sx. 35:65:6 POZ Class "C" + 5% Salt tail in with 200 Sx. Class "C" + 2% CaCl, circulate cement to surface.

4. Drill 7 7/8" hole to 8300'. Run 8300' of 5 1/2" casing as follows: 1300' of 17# J-55 LT&C, 6000' of 15.5# J-55 LT&C, 1000' of 17# J-55 LT&C. Cement in 3 stages with stage tools at 5800' and 3800'. Cement 1st stage with 700 Sx. Class "H" with 5% Microbond, 2nd stage with 575 Sx. Class "C" + 12# Gilsonite/Sx, 3rd stage with 600 Sx. 35:65:6 POZ Class "C" Light cement, tail in with 100 Sx. Class "C" neat, circulate cement to surface.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

[Signature]

TITLE Agent

DATE 11/23/96

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

[Signature]

TITLE

[Signature]

DATE

11/23/97

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

100-443887-100

92000 217002

1990

[illegible]