

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-30038
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. 22948
Lease Name or Unit Agreement Name Baldrige Canyon "11" State Comm.
Well No. 1
Pool name or Wildcat Baldrige Canyon Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
Name of Operator Mewbourne Oil Company	
Address of Operator PO Box 5270, Hobbs, New Mexico 88240 (505)393-5905	
Well Location Unit Letter 11 : 1650 Feet From The South Line and 660 Feet From The West Line 11 Section 24S Township 24E Range NMPM Eddy County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 4174 GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Continuing report of activity ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: New casing strings set and cemented ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

03-31-98

Spudded well on the 03-31-98 at 11:00/am

04-06-98

TD 17 2/1" hole at 430'. Ran 10 jnts. of 13 3/8", 48#, H40, ST & C casing to 430'. Cemented surface casing with 330sx of Hall-Lite "C" with 1/4# per sack flocele, tailed with 200sx of Premium Plus "C" with 2%cc. Plug down at 4:00/pm on the 04-06-98. Cir. 100sx of good cement to pits. Waited on cement for 12 hrs. Tested casing to 500psi before drilling out (ok).

NOTE - WOC - 18hrs

04-12-98

Drilled a 12 1/2" hole to 2645'. Ran 65 jnts of 8 5/8" 32#, J55, ST&C casing to 2645'. Cemented with 250sx of Thixotropic "C" with 1/4# per sack of flocele and 5#/sx Gilsonite, 1000 sx of Interfill "C" with 1/4# per sack flocele and tailed with 250sx of Premium Plus "H" with 2%cc. Plug down at 2:30/pm on the 04-12-98. Cir. 100sx of good cement to pits. Waited on cement for 12 hrs. Tested to 500psi before drilling out. (ok)

NOTE: WOC - 18hrs

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Matthews TITLE Drilling Superintendent DATE 04-15-98

TYPE OR PRINT NAME Steve Matthews

TELEPHONE NO. (505)393-5905

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUN
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE 4-22-98

CONDITIONS OF APPROVAL, IF ANY