Submit 3 Copies to Appropriate District Office

. State of New Mexico Energy, Minerals and Natural Resources Department

CONDITIONS OF APPROVAL, IF ANY:

Form C-103 Revised 1-1-89

DISTRICT I. P.O. Box 1980, Hobbs, NM 88240 DISTRICT II. P.O. Drawer DD, Artesia, NM 88210 DISTRICT III.	OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505		WELL API NO. 30-015-30038 sindicate Type of Lease STATE FEE 6State Oil & Gas Lease No. 22948
1000 Rio Brazos Rd., Aztec, NM 87410			22946
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			rLease Name or Unit Agreement Name Baldridge Canyon "11" State
Type of Well: OIL GAS GAS	OTHER		
WELL WELL W	OTHER		₃Well No.
³ Name of Operator Mewbourne Oil Company			Pool name or Wildcat
Address of Operator PO Box 5270, Hobbs, New Mexico 88240 (505)393-5905			Baldridge Canyon Morrow
4Well Location	Feet From The South	Line and 660	Feet From The West Line
240	Townshin 24E F	Range	NMPM Eddy County
11 Section 24S	10Elevation (Show whether DF,		
4174 GL			
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF IN	TENTION TO:	SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. PLUG AND ANBANDONMENT
PULL OR ALTER CASING		CASING TEST AND CEN	MENT JOB
OTHER: Continuing report of activity		OTHER: New casing	string set and cemented
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed			
05-05-98 TD 7 7/8" hole at 10,850'. Ran 247 jnts of 5 1/2" 17# N80 LT&C. Set casing at 10,850'. Cemented in two stages TD 7 7/8" hole at 10,850's of Super Premium with 5#/sx Gilsonite, 1#/sx Salt, 0.4% CFR-3, 0.5% Halad 344. First stage cement 500sx of Super Premium with 5#/sx Gilsonite, 1#/sx Salt, 0.4% CFR-3, 0.5% Halad 344. Plug down at 2:45/pm, 05-04-98. Second Stage: 700sx of Halco Lite Premium with 5#/sx Salt, 1/4#/sx Flocele 0.3% Halad 322, Plug down at 10:00/pm 05-04-98 Est. top of cement at 2100'.			
		december 1	CO. HELSIN
I hereby certify that the intermation above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Drilling Superintendent DATE 05-05-98			
SIGNATURE The I	(ackeurs)	TITLE Driving Supering	
TYPE OR PRINT NAME Steve Matthews	}		TELEPHONE NO. (505)393-5905
(This space for State Use)		TITLE	DATE 5-20-98