

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Melbourne Oil Co.</u>		Lease <u>Baldridge Canyon St Cam</u>		Well # <u>2</u>	
Location of Well	Unit <u>G</u>	Section <u>11</u>	Township <u>24</u>	Range <u>24</u>	County <u>Edley</u>
Drilling Contractor			Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48^{xx}</u>	<u>400</u>	<u>400</u>	<u>Circ.</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>32^{xx}</u>	<u>2700</u>	<u>800</u>	<u>Circ.</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17^x</u>	<u>10800</u>	<u>1000</u>	<u>Tie back</u>
Casing Data:					
Surface <u>63</u> joints of <u>8 5/8</u> inch <u>32^{xx}</u> # Grade <u>J-55</u>					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>800</u>					
Type of Shoe used <u>Texas</u> Float collar used <u>yes</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>2655</u> Set <u>2660</u> Feet of <u>8 5/8</u> Inch <u>32^{xx}</u> # Grade <u>J-55</u>					
New used csg. @ <u>8 5/8</u> with <u>250</u> sacks neat cement around shoe					
+ _____ sacks additives <u>1/4^{xx}</u> Cello <u>10</u> / <u>10</u> <u>gibsonite</u>					
Plug down @ <u>11:00</u> (AM) (PM) Date <u>11/18/96</u>					
Cement circulated <u>yes</u> No. of Sacks <u>150</u> <u>sxs</u> <u>to pit</u>					
Cemented by <u>B.J. Hughes</u> Witnessed by <u>[Signature]</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					