

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-015-30462

Indicate Type of Lease
STATE ☒ FEE ☐

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name
Baldridge Canyon #2 State Corn.

Well No.
#2

Pool name or Wildcat
Baldridge Canyon Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

Name of Operator
Mewbourne Oil Company

Address of Operator
PO Box 5270, Hobbs, New Mexico 88240 (505-393-5905)

Well Location
Unit Letter G : 1650 Feet From The North Line and 1650 Feet From The East Line
Section 24 south Township 24 east Range NMPM Eddy County
Elevation (Show whether DF, RKB, RT, GR, etc.)
4130 GR

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐


Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well on the 11-12-98

Drilled a 17 1/2" hole and set 13 3/8", 48#, H40, ST&C set @ 463'. Cemented with 200 sks of Class "H" Thickset + 10% A-B10 + 1/4# / sk Celloflake + 10# / sk Gilsonite + .5% cc. 200 sks of BJ Lite + 6% Gel + 1/4# / sk Celloflake. Tailed with 200 sks of Class "C" + 2%cc. Plug down at 12:45/pm 11/13/98. Circulated 150 sks to the pits.

Drilled a 12 1/4" hole and set 8 5/8", 32#, J55, ST&C @ 2655'. Cemented with 250 sks of Thickset "H" + 10% A-10B + 10#/sk Gilsonite + 1/4# / sk Celloflake + .5% cc. 1000 sks of BJ Lite + 1/4# / sk Celloflake. Tailed with 250 sks of Class "C" + 2%cc. Plug down at 10:30/am 11/18/98. Circulated 150 sks to pits.

City Well Name



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Matthews TITLE Drilling Superintendent

DATE 11-30-98

TYPE OR PRINT NAME Steve Matthews

TELEPHONE NO. 393-5905

(This space for State Use)

APPROVED BY Jim W. [Signature]

TITLE District Supervisor

DATE 12-1-98

CONDITIONS OF APPROVAL, IF ANY: