

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsf
bp

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-31004
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 001786
7. Lease Name or Unit Agreement Name James Ranch Unit
8. Well No. 67
9. Pool name or Wildcat Quahada Ridge (Delaware); Southeast

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator Bass Enterprises Production Co.	
3. Address of Operator P.O. Box 2760 Midland, TX 79702-2760	
4. Well Location Unit Letter <u>L</u> : <u>1874'</u> Feet From The <u>South</u> Line and <u>1096'</u> Feet From The <u>West</u> Line Section <u>36</u> Township <u>22S</u> Range <u>30E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:


PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Surface Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 11" hole to 3810' 4/5/00.
Ran 57 joints 8-5/8" 32#, J55 LT&C casing set (0-2516') and 30 joints 8-5/8" 32# J-55, HCK55, CF-50 LT&C casing set (2516-3810').
Cemented with 700 sacks 50/50 Poz C with additives. Tail with 250 sacks Class C with additives.
Circulated 125 sacks to surface. WOC 26-1/2 hours.
Drill cement, test casing to 1000 psi, OK 4/7/00.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tami Wilber TITLE Production Clerk DATE 6/9/00

TYPE OR PRINT NAME Tami Wilber TELEPHONE NO. 915-683-2277

(This space for State Use)

Jim W. Burns

SUPERVISOR, DISTRICT II

APPROVED BY BGA TITLE _____ DATE JUN 15 2000

CONDITIONS OF APPROVAL, IF ANY: