

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTSUBMIT IN  
811 Other Inst  
reversATE  
onFORM APPROVED  
OMB NO. 1004-0136  
Expires: February 28, 1995

## APPLICATION FOR PERMIT TO DRILL OR DEEPEN

## 1a. TYPE OF WORK

DRILL ☒DEEPEN ☐

## b. TYPE OF WELL

OIL  
WELL ☒GAS  
WELL ☐

OTHER

SINGLE  
ZONE ☒MULTIPLE  
ZONE ☐

## 2. NAME OF OPERATOR

POGO PRODUCING COMPANY

(RICHARD WRIGHT 915-685-8140) 17891

## 3. ADDRESS AND TELEPHONE NO.

P.O. BOX 10340 MIDLAND, TEXAS 79702-7340 915-685-8100

## 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface 1900' FNL &amp; 1650' FWL SEC. 34 T23S-R31E EDDY CO. NM

At proposed prod. zone SAME

Unit F

RILLINGTON

## 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

Approximately 25 miles East of Living New Mexico

## 15. DISTANCE FROM PROPOSED

LOCATION TO NEAREST  
PROPERTY OR LEASE LINE, FT.  
(Also to nearest drilg. unit line, if any)

1650'

18. DISTANCE FROM PROPOSED LOCATION  
TO NEAREST WELL, DRILLING, COMPLETED,  
OR APPLIED FOR, ON THIS LEASE, FT.

990'

## 16. NO. OF ACRES IN LEASE

640

17. NO. OF ACRES ASSIGNED  
TO THIS WELL

40

## 21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3439' GR.

## 20. ROTARY OR CABLE TOOLS

ROTARY

## 22. APPROX. DATE WORK WILL START

AS ORDERED BY APPROVED WATER BASIN

## PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	CONDUCTOR 20"	NA	40'	Cement to surface with Redi-mix
14 3/4"	H-40 10 3/4"	32.75	750'	700 Sx. circulate to surface
9 7/8"	J-55 7 5/8"	26.4	4250'	1100 Sx. " " "
6 3/4"	J-55 4 1/2"	11.6	8500'	1500 Sx. " " "

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
2. Drill 14 3/4" hole to 750'. Run and set 750' of 10 3/4" H-40 32.75# ST&C casing. Cement with 700 Sx. of Class "C" cement + additives, circulate cement to surface.
3. Drill 9 7/8" hole to 4250'. Run and set 4250' of 7 5/8" J-55 26.4# ST&C casing. Cement with 1100 Sx. of Class "C" cement + additives, circulate cement to surface.
4. Drill 6 3/4" hole to 8500'. Run and set 8500' of 4 1/2" J-55 11.6# LT&C casing. Cement in two stages, DV Tools at 6200' & 3900'± Cement with 1500 Sx. of Class "H" cement + additives, circulate cement to surface.

Notify OCD at SPUD & TIME  
to witness cementing the  
7 3/8" casing.APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS

ATTACHED

ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present well and proposed new productive zone. If proposal is to drill or open directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give brief description of preventive program, if any.

SIGNED Art Janice TITLE Agent

DATE 01/27/00

(This space for Federal or State office use)

PERMIT NO.

APPROVAL

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY 3/1/00 Splenda RIA TITLE Acting State Director

DATE 4.11.00

\*See Instructions On Reverse Side

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations.

APPROVED FOR 1 YEAR

