to Appropriate District Office	Energy, Minerals and I	Natural Resources Department	COS Revised 1.1 pc
DISTRICT I	OL CONSERV	VATION DIVISION	Revised 1-1-89
P.O. Box 1980, Hobbs, NM 88240			U
DISTRICT II	Canta Es Na	Box 2088	30-015-31402
P.O. Box Drawer DD, Artesia, NM 882	10 Santa Fe, New	/ Mexico 87504-2088	5. Indicate Type of Lease STATE FEE
DISTRICT III			<del></del>
1000 Rio Brazos Rd., Aztec, NM 8741			6. State Oil / Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT  (FORM C-101) FOR SUCH PROPOSALS.)			7. Lesse Name or Unit Agreement Name REMUDA BASIN '31' STATE
1. Type of Well: OIL GAS WELL WELL		OALO.,	MEMORY BROWN OF STATE
2. Name of Operator TEXACO EX	PLORATION & PRODUCTION	ON INC.	8. Well No.
	9, Midland Texas 79702		9. Pool Name or Wildcat
4. Well Location			
Unit Letter <u>F</u> : <u>1980</u> Feet From The <u>NORTH</u> Line and <u>2310</u> Feet From The <u>WEST</u> Line			
Section 31	•	Range 30-E NM	PMEDDY COUNTY
	10. Elevation (Show wheth	ner DF, RKB, RT,GR, etc.) GR-3127	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTIO		1	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	
· <u>L</u>	CHANGE PLANS		ALTERING CASING
	ONANGE I DANG	COMMENCE DRILLING OPER	<u></u>
OTHER:		CASING TEST AND CEMEN	T JOB
omen.		U OTHER:	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  TOTAL DEPTH OF WELL WILL BE 7450 CHANGING FROM 7500 OF CHANG			
TOTAL DEPTH OF WELL WILL BE 7150' CHANGING FROM 7500' ORIGINALLY PERMITTED BY BASS ENTERPRISES PRODUCTION CO.			
CEMENT AND CASING PROGRAM WIL 14 3/4" HOLE SIZE 11 3/4" CSG. SIZ 11" HOLE SIZE 8 5/8" CSG. SIZ	ZE 24# CSG. WEIGHT/F	OOT 400 SETTING DEPTH	400 SX CEMENT CIRCULATE 850 SX CEMENT CIRCULATE
8 7/8" HOLE SIZE 5 1/2" CSG. SIZ			850 SX CEMENT CIRCULATE 1700 SX CEMENT CIRCULATE
CEMENTING PROGRAM: SURFACE CASING: 400 SACKS CLASS C w/2% GEL, 2% CaCl2 (14.8 PPG, 1.34 CF/S, 6.40 GW/S). INTERMEDIATE CASING: 750 SACKS 35/65 POZ CLASS H w/6% GEL, 5% SALT, 1/4# FC (12.4 PPG, 2.14 CF/S, 10.46 GW/S). F/B 100 SACKS CLASS H NEAT (15.6 PPG, 1.18 CF/S, 5.20 GW/S). PRODUCTION CASING: 1000 SACKS 50/50 POZ CLASS H w/2% GEL, 5% SALT, 1/4# FC (14.2 PPG, 1.35 CF/S, 6.30 GW/S). F/B 600 SACKS 35/65 POZ CLASS H w/6% GEL, 5% SALT, 1/4# FC (12.4 PPG, 2.14 CF/S, 10.46 GW/S). F/B 100 SACKS CLASS H NEAT (15.6 PPG, 1.18 CF/S, 5.20 GW/S).			
I hereby certify that the information aboys is true and complete	e to the best of my knowledge and belief.		
SIGNATURE M. Paul Pape	TITLE C	<u>Commission Coom</u>	dinator DATE 12/4/00
TYPE OR PRINT NAME A. Phil	Ryan		Telephone No. 688-4606
(This space for State Use)	MAI DIGITAL BOX	F(0, C) 200	<b>BB</b> - 0
ORIGI	val signed by time ict in superviside.	w. 50%	DATE <b>CEC 0 6 2000</b>
CONDITIONS OF APPROVAL, IF ANY:	······································		DeSato/Nichais 10-94 ver 2.0