Submit 3 Copies to Appropriate District Office	State of New Me Energy, Minerals and Natural Re		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATIO	WELL API NO.	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210			30-015-31439 sIndicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			STATE FEE FEE
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			PLease Name or Unit Agreement Name ,
Type of Well: OIL GAS WELL WELL OTHER			
2Name of Operator	2Name of Operator		Well No.
Pogo Producing Company /			4 RECEIVESIA
P. O. Box 10340, Midland, TX 79702-7340			Cedar Canyon Delaware
•Well Location Unit Letter :1650	Feet From The South	Line and 1300	Feet From The West 2000 Line
Section 21 Township 24 Range 29 NMPM Eddy County			
10Elevation (Show whether DF, RKB, RT, GR, etc.) 2938			
¹¹ Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBS			SEQUENT REPORT OF:
PERFORM REMEDIAL WORK			ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OF	PNS. PLUG AND ANBANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEME		
			rface & intermediate casing
12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			
Spud & Set Surface Csg - MIRU Big Dog #3. Spud well @ 1600 hrs 12/02/00. Drld 12" hole to 584'. Ran 14 jts 8-5/8" 32# J-55 ST&C csg. TPGS @ 584'. BJ cmt'd w/ 255 sks 65:35 POZ "C" @ 12.8 ppg followed by 150 sks CI "C" + 2% CaCl2 @ 14.8 ppg. Plug down @ 1930 hrs 12/03/00. Circ 121 sks to surface. WOC 38-1/2 hrs. Make cut-off. Weld on WH & test to 2000# ok.			
Production Csg - Drld 7-7/8" hole to 5420'. TD reached @ 12/19/00. Logged well w/ Baker Atlas. Ran 125 jts 5-1/2" 15.5# J-55 LT&C csg. Benoit shoe @ 5400'. Float collar @ 5352'. DV tool @ 3020'. Bj cmt'd 1st stage w/ 575 sks CI "C" + .15% FL52 + .75% CD32 @ 14.1 ppg. Circ 50 sks to surface. Cmt'd 2nd stage w/ 570 sks 35:65 POZ @ 12.4 ppg followed by 100 sks CI "C" + 1% CaCl2 @ 14.8 ppg. Plug down @ 1430 hrs 01/10/01. ND BOP's & make cut-off. Weld on WH. CBL ran 01/17/01. TOC @ 2940'.			
I hereby certify that the information above is to SIGNATURE	1 1	ge and belief. _{LE} Operation Tech	DATE 02-06-01
TYPE OR PRINT NAME Cathy Tomberlin			TELEPHONE NO. 915-685-8100
(This space for State Use)	MOU		
	NGNED BY TIM W. GUM	LE	FEB 1 2 2001

.