

Submit 3 Copies to Appropriate  
District Office  
DISTRICT I

1625 n. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

2040 S. Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco  
Santa Fe, NM 87505

RECEIVED  
OCD - ARTESIA

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-31757

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

4538

7. Lease Name or Unit Agreement Name:

Saragossa "10" State

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Dominion Oklahoma Texas Exploration & Production, Inc.

8. Well No.

1

3. Address of Operator

14000 Quail Springs Parkway - Suite 600 - Oklahoma City, OK 73134

9. Pool name or Wildcat

4. Well Location

Unit letter A 660' feet from the North line and 1290' feet from the East line.

Section 10 Township 23S Range 26E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, Gr, etc.)  
3291'

**11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data**

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐

OTHER: Plug Back. ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Verbal approval received to come up hole. 3/9/02 set CIBP @ 11,600', dump bailed 35' of cement on top. Perf'd Atoka as follows: 10,966 - 10,986 4 spf. 3/12/02 acidized w/3000 gal 15% NeFe acid w/clay control and 100 ball sealers. 3-14-02 set CIBP @ 10,920', dump bailed 35' of cement on top. Perf'd Atoka as follows: 10,796' - 10,800', 10,850' - 10,857' 4 spf. 3/16/02 acidized w/1500 gal 15% NeFe acid w/clay control and 10% methanol w/75 ball sealers. Flow testing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carla Christian TITLE Regulatory Technician DATE 03/21/02

Type or print name Carla Christian

Telephone No. 405-749-5263

(This space for State use)

APPROVED BY [Signature] ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR TITLE

DATE MAR 29 2002

Conditions of approval, if any: