

7" Intermediate

Cement with 250 sx Modified "C" + additives in Stage 1. Cement Stage 2 with 600 sx 35:65 Poz "C" + additives & 200 sx Class "H" cement + additives. DV tool @ 9500'.

4 ½" Liner

Cement with 250 sx Class "H"

#### V. Proposed Mud System:

<u>DEPTH</u>	<u>Type</u>	<u>Wt</u>	<u>Vis</u>	<u>WLF</u>
0' - 400'	Fresh water	8.4	30	NC
400'-2650'	Fresh water	8.4	30	NC
2650'-11250'	Cut Brine	8.4-9.2	30-36	25
11250-12750	Cut Brine	9.8-10.2	32-40	10

The mud system will consist of a 5-7 mil plastic-lined reserve pit.

#### VI. Proposed Control Equipment:

See Exhibit "H" for BOP layout.

#### VII.- Auxiliary Equipment:

Blowout preventor, gas detector, kelly cock, pit level monitor, flow sensors, and stabbing valve.

#### VIII A. Testing Program:

Drillstem tests will be run on the basis of drilling shows.

#### B. Logging Program:

The electric logging program will consist of GR-Dual Laterolog-MSFL from TD to surface casing and GR-Compensated Neutron-Density from TD to surface.

#### C. Coring Program:

No conventional coring is anticipated.