	·						•	Brm				
·			•							Bruch		
										Sty	<b>. .</b>	
DISTRICT I State of New Mexico 22 22 5 Form C-10											Form C-101	
1625 N. French Dr., Hobbs, NM 88240 Energy, Minerals and Natura							es Dep	artment ्	3.	Rej	ised March 17, 1999 Instructions on back	
DISTRICT II 811 South First, Artesia, NM 88210 OIL CONSERVAT							лэж	<b>₹</b> Kinaa	Pop Supi		priate District Office	
DISTRICT II	ıı			OIL CO	PQ BOX							
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87504-2088 ARTEC.												
DISTRICT IV 2040 South Pacheco, Santa Re, NM 8750.  AMENDED REPORT												
								ائ مانا هو	<u> </u>			
APPL	ICATIO			TO DI	RILL, RE-E	ENTER, B	REE	M. PLUC		K, OR A	DD A ZONE	
Yates Petroleum Corporation									025575			
105 South Fourth Street									- ` ^	API Number		
Artesia, N				México 8	Property Na			30- O/S	<u> </u>	- 51911 6 Well No.		
12328				. 0	Fraham AKE			5				
<sup>7</sup> Surface Location												
UL or lot no. Section 2		Township	Ownship Range 22S 31E		Feet from the	North/South Line . Fe		Feet from the	1		County .	
		0		Rottom	330   <b>Hole Loc</b> a	North	liffer	2310 ent Fron	L.,	est	Eddy	
UL or lot no.	Section	Township	Ránge	Lot Idn	Feet from the	North/South		Feet from the		est Line	County	
		,	.5									
<sup>9</sup> Proposed Pool 1												
	Undesi	gnated Lo	st Tank	Delawai	re	PLEASE	NOT	EATTAC	HED PO	OTASH A	AGREEMENT.	
Work Type Code 12 Well Type Code Cable/						Rotary Lease Type Code TS Ground Level Elevation					Level Elevation	
N			0			R ·		S			3514'	
<sup>16</sup> Multiple N			<sup>17</sup> Proposed Depth 8400'		Formation Delaware		Not Determined		20 Spud Date ASAP			
	21 Proposed Casing and Cement Program											
Hole	Size	Casing			weight/feet	Setting I		1	f Cement	F.	stimated TOC	
17 1/2"			13 3/8"		48#		850'		Sacks of Cement 450 SX		Surface	
11"		8 5/	8 5/8"		32#		4100'		1400 sx		Surface	
7 7/8"		5 1/	5 1/2"		15.5# + 17#		8400'		Stage 1-400sx		TOC-6200'	
					· · · · · · · · · · · · · · · · · · ·	DV Tool@4050		' Stage 2	Stage 2-375sx		Surface	
<sup>22</sup> Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive												
					onal sheets if nec							
					o drill and to							
	Approximately 850' of surface casing will be set and cement circulated to shut off gravel and cavings.  Intermediate casing will be set at 4100' and cemented to surface. If commercial, production casing will be											
									aı, prod	uction ca	asing will be	
run and cemented, will perforate and stimulate as needed for production.  MUD PROGRAM: 0-850' FW/Native Mud; 850'-4100' Brine; 4100'-6800' Cut Brine; 6800'-8400' Cut												
	Brine/Starch.											
					be installed	on the 8 $\hbar$	i/8" ca	sing and t	tested c	laîly.		
	1 hereby certify that the information given above is true and complete to the best o my knowledge and belief.											
Signature:		Approved by: ORIGINAL SIGNED BY TIM W. GUM										
Printed name		Title: DISTRICY U SUPERVIOUR										
Title: Regulatory Agent						Approval Date	JUL	2 4 20	expiration	n Date:	O A Geno	
Date:	07/24/01	ı		Phone: (505) 749 1471			Conditions Attached NOTIFY OCD SPUD & TIME TO WITNESS					
	01/24/0	I	L(;	(505) 748-1471			CEMI	EMTING OF	ALL CA	SING STR	MCS	