

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-015-3202#7

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-2597

7. Lease Name or Unit Agreement Name:

Flora AKF State

7. Well No.

3

8. Pool name or Wildcat

Undesignated Lost Tank
Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter L : 2310 feet from the South line and 330 feet from the West line

Section 2 Township 22S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3513' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER:

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud and set casing

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded at 8:30 AM 6-2-02. Set 40' of 20" conductor. Resumed drilling at 6:00 PM 6-3-02. TD 17-1/2" hole at 9:30 PM 6-4-02. Ran 19 jts. 13-3/8" 48# H-40 casing set at 850'. Texas pattern guide shoe set at 850'. Insert float set at 805'. Cemented with 850 sx BJ Lite C with additives. Tailed in with 250 sx Class "C" with additives. PD at 4:45 AM 6-5-02. Circulated 143 sx. Resumed drilling at 6:00 AM 6-6-02. WOC 25 hrs. and 15 min. Reduced hole to 11". TD 11" hole at 5:00 AM 6-12-02. Ran 97 jts. 8-5/8" 32# J-55 casing set at 4105'. Regular guide shoe set at 4105'. Float collar set at 4062'. Cemented with 1275 sx BJ Lite "C" with additives. Tailed in with 250 sx Class "C" with additives. PD at 6:00 PM 6-12-02. Circulated 145 sx. WOC 24 hrs. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 17, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)
ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY Tina Huerta TITLE Regulatory Compliance Supervisor DATE JUN 25 2002

Conditions of approval, if any: