

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-32028

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Flora AKF State

8. Well No.

4

9. Pool name or Wildcat

Undesignated Lost Tank
Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation /

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter M : 990 feet from the South line and 330 feet from the West line

Section 2 Township 22S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3510' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING
CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: Set production casing ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/15/02 - Reached TD 8350' at 9:30 PM.

12/17/02 - Ran 195 joints 5-1/2" 17# and 15.5# J-55 casing set at 8350' as follows: 31 joints SB (1303.63'), 25 joints SB (1055.68'), 133 joints Varn (5743.88'), 6 joints varn (256.58'). Davis-Lynch float shoe set at 8378'. Davis-Lynch float collar set at 8334'. Davis-Lynch packer stage collar set at 4035' to 4053'. Bottom marker from 7046' to 7068'. Top marker from 5991' to 6012'. Stage 1: Cemented with 425 sx Super "H" with additives (yld 1.72, wt 13). Tailed in with 50 sx Thixset (yld 1.42, wt 14.4). Stage 2: Cemented with 450 sx Interfill "C" (yld 2.41, wt 11.9). Tailed in with 100 sx Premium Plus + additives (yld 1.32, wt 14.8). Circulated 72 sx. NOTE: Pumped 150 bbls with 150 SCF/bbl N2 and 12 bbls Super Flush-102 ahead of 1st stage.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE December 27, 2002

Type or print name Tina Huerta

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT H SUPERVISOR

JAN 06 2003

APPROVED BY Tina Huerta TITLE Regulatory Compliance Supervisor DATE December 27, 2002

Conditions of approval, if any: