Submit 3 Copies to Appropriate District Office

Ener

State of New Mexico **linerals and Natural Resources Department**

Form C-103 evised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

2040 Pacheco St. Santa Fe. NM 87505

30-015-32133

DISTRICT II Santa Fe, INVI 67505	
P.O. Drawer DD, Artesia, NM 88210	sIndicate Type of Lease
DISTRICT III	STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410	6State Oil & Gas Lease No.
	V-314
SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	7Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.)	Outlaw Flats 2 State Com
Type of Well:	
OIL GAS WELL WELL OTHER	
2Name of Operator	«Well No.
Mewbourne Oil Company	1
3Address of Operator	Pool name or Wildcat
PO Box 5270, Hobbs, New Mexico	Baldridge Canyon Morrow
4Well Location	
Unit Letter 1 : 660 Feet From The North Line and 1310 Feet From The East Line	
Section 2 Township 24S Range 24E	NMPM Eddy County
oElevation (Show whether DF, RKB, RT, GR, etc.) 3972' GL.	
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
NOTICE OF INTENTION TO.	SEQUENT REPORT OF.
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING O	PNS. PLUG AND ANBANDONMENT
PULL OR ALTER CASING CASING TEST AND CEME	ENT JOB X
OTHER:	
12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	
12/21/01MI & RU. Spud 17 1/2" hole.	
12/22/01 TD'od 17 1/2" holo @ 419! Don 419! 12 2/2" 49# H 40 CT/C and Comparted and CFO also D H to FOL 1 and CFO	
12/22/01TD'ed 17 1/2" hole @ 418'. Ran 418' 13 3/8" 48# H-40 ST/C csg. Cemented w/ 250 sks BJ Lite 'C' w/ additives. Mixed @ 12.5 #/g w/ 1.98 cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8#/g w/ 1.34 cf/sk yd. Circl 50 sks to pit.	

WOC 18 hrs. Tested BOP & equipment to 1000 psi. OK. Drill out w/ 12 1/4" bit.

12/28/01...TD'ed 12 1/4" hole @ 2618'. Ran 2618' 8 5/8" 32# J-55 ST/C csg. Cemented w/ 850 sks BJ Lite 'C' w/ additives. Mixed @ 12.5 #/g w/ 1.98 cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8#/g w/ 1.34 cf/sk yd. Circl 74 sks to pit. WOC 18 hrs. Tested BOP & equipment to 2500 psi. OK. Drill out w/ 7 7/8" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE District Manager 12-31-01 SIGNATURE TYPE OR PRINT NAME N.M. Young TELEPHONE NO. 505-393-5905

DATE

(This space for State Use

APPROVED BY

Tim W. Bum

SUPERVISOR, DISTRICT II

JAN 28 2002

CONDITIONS OF APPROVAL, IF ANY: