

complied with.

5. Trash, waste paper, garbage and junk will be collected in steel trash bins and removed after drilling and completion operations are completed. All waste material will be contained to prevent scattering by the wind.
6. All trash and debris will be removed from the wellsite within 30 days after finishing drilling and/or completion operations.
8. Ancillary Facilities
 1. None needed.
9. Wellsite Layout
 1. The location and dimensions of the well pad, mud pits, reserve pit and location of major rig components are shown on the well site layout sketch exhibit "D".
 2. Leveling of the wellsite will be required with minimal cuts or fills anticipated.
 3. The reserve pit will be plastic lined.
 4. The pad and pit area have been staked and flagged.
10. Plans for Restoration of the Surface
 1. After completion of drilling and/or completion operations, all equipment and other materials not needed for operations will be removed.
 2. Pits will be filled and location cleaned of all trash and junk to leave the well site in as aesthetically pleasing condition as possible. Any plastic material used to line the pits or sumps will be cut off below ground level as far as possible and disposed of before the pits are covered. All unattended pits containing liquid will be fenced and the liquid portion allowed to evaporate before the pits are broken and backfilled.
 3. After abandonment of the well, surface restoration will be in accordance with BLM guidelines. This will be accomplished as expeditiously as possible. Barring unforeseen problems, all pits will be filled and leveled within 90 days after abandonment.