

5. Drainage Design: N/A
 6. Culverts: N/A
 7. Cuts and Fills: N/A
 8. Gates and Cattlegaurds: N/A
3. Existing wells within one mile radius of the proposed well are shown on exhibit "C".
 4. Location of Existing and/or Proposed Facilities
 1. If the well is productive, production facilities will be constructed on the well pad. The facility will consist of a separator, 4'x 20' heater treater, two 270 bbl oil tanks and one 270 bbl fiberglass water tank, all tanks will be low profile, 8' high. All permanent above ground facilities will be painted in accordance with the BLM's painting guidelines simulating the color of the surroundings.
 2. All site security guidelines identified in 43 CFR 3162.7 regulations will be adhered to and a site security plan will be submitted for the Saragossa 4 Federal #3 tank battery. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed.
 5. Location and Type of Water Supply

Fresh water and brine water will be used to drill this well. It will be purchased from a local source and transported to the well site.
 6. Source of Construction Materials

Caliche will be hauled from a federal Caliche pit.
 7. Method of Handling Waste Disposal
 1. Drill Cuttings will be disposed of in drilling pits.
 2. Drilling fluids will be allowed to evaporate in the drilling pits until pits are dry.
 3. Water produced during tests will be disposed of in the drilling pits. Oil produced during tests will be stored in test tanks until sold.
 4. Current laws and regulations pertaining to the disposal of human waste will be