Submit 3 Copies State of New Mexico Form C-103 to Appropriate Revised 1-1-89 inerals and Natural Resources Department Energ District Office DISTRICT I **OIL CONSERVATION DIVISION** P.O. Box 1980, Hobbs, NM 88240 WELL APINO 2040 Pacheco St. 30-015-32400 Santa Fe, NM 87505 sIndicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE X STATE DISTRICT III State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 V-5319 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFREN OR PLUE BACKATO A 7Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR BERMIT" Rustler Breaks 26 Fee Com (FORM C-101) FOR SUCH PROPOSALS.) 2/4181815181518 Type of Well: WELL OTHER WELL aWell No. 2Name of Operator Mewbourne Oil Company 14744 / 3Address of Operator Pool name or Wildcat PO Box 5270 Hobbs, N.M. 88241 Salt Draw Atoka 4Well Location 900 South West Unit Letter \_ Feet From The \_ Feet From The 26 Eddy County Township Range 10Elevation (Show whether DF, RKB, RT, GR, etc. 2954' GL Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PERFORM REMEDIAL WORK CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: 12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 09-27-02...Spud 17 1/2" hole. Drilled to 325'. Ran 325' 13 3/8" H-40 48# ST&C casing. Cemented w/ 200 sks 65/35 C/Poz w/ 6% gel & additives. Mixed @ 12.5 #/g w/ 1.97 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 60 sks to pit. WOC 18 hrs. NU BOP & test equipment to 500 psi. OK. Drill out w/ 12 1/4" bit. 10-08-02...TD'ed 12 1/4" hole @ 4628'. Ran 4628' 9 5/8" 40# N&J LT&C casing. Cemented w/ 1250 sks 65/35 C/Poz w/ 6% gel & additives. Mixed @ 12.5 #/g w/ 2.04 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 80 sks to pit. WOC 18 hrs. NU BOP & test equipment to 2500 psi. OK. Drill out w/ 8 3/4" bit.

I hereby certify that the information above is true and complete to	he best of my knowledge and belief.	
SIGNATURE SIGNATURE	TITLE District Manager	DATE 10-18-02
7. 7		
TYPE OR PRINT NAME N.M. Young		TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY

ORIGINAL SIGNED BY TIM W. GUM METRICT II SUPERVISOR

DATE NOV 1 2 2002