Form 3160-5 (June 1990)

## Oil Cons. DEPARTMENT OF THE INTERNATIONAL PROPERTY OF LAND MANAGEMENT AVENUE Artesia, NM 88210 SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. NMNM-14473

6. If Indian, Allottee or Tribe Name

158

|  | ERMIT-" for such proposals  | 7. If Unit or CA, Agreement Designation  |
|--|---|--|
| SUBMIT IN T  | FRIPLICATE  |  |
| Type of Well Oil Gas   | 3031-12325  | 8, Well Name and No.   |
| Well Well Other  |   | West Loving 11 Federal Com #1  |
| Name of Operator   |   |  |
| Mewbourne Oil Company 14744  | <u> </u>  | 9. API Well No.<br>30-015-32499  |
| Address and Telephone No.<br>PO Box 5270, Hobbs, N.M. 88241. 505-393-5905  | RECEIVED OCD - ARTESIA  | 10. Field and Pool, or Exploratory Area  |
| Location of Well (Footage, Sec., T., R., M., or Survey Descriptio  | OCD - ARTESIA   | Black River Morrow   |
|  |   | 11. County or Parish, State  |
| 660' FNL & 660' FEL Unit Letter A of Sec.11 T-24   | S R-27E   | Eddy Co., N.M.   |
|  |   |  |
|  | INDICATE NATURE OF NOTICE, REPORT   |  |
| TYPE OF SUBMISSION   | TYPE OF ACTIO   |  |
| Notice of Intent   | Abandonment   | Change of Plans  |
|  | Recompletion  | New Construction   |
| Subsequent Report Final Abandonment Notice   | Plugging Back   | Non-Routine Fracturing   |
|  | Casing Repair   | ☐ Water Shut-Off   |
|  | Altering Casing   | Conversion to Injection  |
|  | Other TD & Production Csg   | (Note: Report results of multiple completion on Well<br>Completion or Recompletion Report and Log form.)   |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-LC   | Il pertinet details, and give pertinent dates, including estimated of and true vertical depths for all markders and zones pertinent to the organization ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C case ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 | sing. Cemented in 2 stages<br>sks 'H' w/ additives. Mixed  |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Low/700 sks Super 'H' Modified w/ additive # 45.4.4% \$ 4.28 yd Open DV Tool @   | ogs Ran12 815' of 5 1/2" N&P110 17# LT&C cas  | sing. Cemented in 2 stages<br>sks 'H' w/ additives. Mixed<br>nd stage w/ 900 sks BJ Lite 'H'   |
| 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Lo w/ 700 sks Super 'H' Modified w/ additiv   | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas<br>ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475   | sing. Cemented in 2 stages<br>sks 'H' w/ additives. Mixed<br>nd stage w/ 900 sks BJ Lite 'H'   |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Low/ 700 sks Super 'H' Modified w/ additive @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 y   | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas<br>ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475<br>§ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2<br>yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &  | sing. Cemented in 2 stages<br>sks 'H' w/ additives. Mixed<br>nd stage w/ 900 sks BJ Lite 'H'   |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Low/ 700 sks Super 'H' Modified w/ additive @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 yd. 12-13-02Set slips & Released Rig.                               | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &   | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.   |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Low w/ 700 sks Super 'H' Modified w/ additive @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 yd. 12-13-02Set slips & Released Rig.                             | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &   | sing, Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.   |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Lo w/ 700 sks Super 'H' Modified w/ additiv @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 y 12-13-02Set slips & Released Rig. 12-19-02Ran CBL. TOC @ 4934'.   | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &   | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.  ED FOR RECORD  C 3 1 2002                            |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Lo w/ 700 sks Super 'H' Modified w/ additive @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 y 12-13-02Set slips & Released Rig.  12-19-02Ran CBL. TOC @ 4934'. | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &   | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.  ED FOR RECORD  C 3 1 2002                            |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Lo w/ 700 sks Super 'H' Modified w/ additive @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 y 12-13-02Set slips & Released Rig.  12-19-02Ran CBL. TOC @ 4934'. | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &  ACCEPTE  DEC                                   | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.  ED FOR RECORD  C 3 1 2002  S C. SWOBODA EUM ENGINEER |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Low/700 sks Super 'H' Modified w/ additive@ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 yd. 12-13-02Set slips & Released Rig.  12-19-02Ran CBL. TOC @ 4934'.  | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g & ACCEPTE DEC                                     | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.  ED FOR RECORD  C 3 1 2002  S C. SWOBODA EUM ENGINEER |
| directionally drilled, give subsurface locations and measured at 12-10-02TD'ed 8 3/4" hole @ 12,815'. Ran E-Lo w/ 700 sks Super 'H' Modified w/ additiv @ 15.1 #/g & 1.28 yd. Open DV Tool @ w/ additives. Mixed @ 12.5 #/g & 1.95 y 12-13-02Set slips & Released Rig.                                 | ogs. Ran12,815' of 5 1/2" N&P110 17# LT&C cas ves. Mixed @ 13.8 #/g & 1.40 yd. Followed w/ 475 @ 8986'. Circl 60 sks to pit. Circl 6 hrs. Cemented 2 yd. Tailed w/ 100 sks 'H' neat. Mixed @ 15.6 #/g &  ACCEPTE  DEC                                   | sing. Cemented in 2 stages sks 'H' w/ additives. Mixed nd stage w/ 900 sks BJ Lite 'H' 1.18 yd. Est TOC @ 4500'.  ED FOR RECORD  C 3 1 2002  C C SWOBODA  EUM ENGINEER |

FILE CONTROL OF OF