

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN THE "CATE"  
(Other instructions on re-  
verse side)Form approved,  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L.C. 061716

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government "134"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Washington Ranch (Morrow)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Section 12-26S-24E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. BOX 71, CONROE, TEXAS 77301

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FNL &amp; 660' FEL OF SECTION 12

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

RKB: 3879

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well has been shut-in since 5-21-75. Present perforations are 7452-57, 7462-64, 7470-78. Present PBTD is 7520'. Top of cement outside 7" casing is estimated from temperature survey at 6000'. Intermediate 9-5/8" casing is cemented from 4663' to surface. Surface 13-3/8" casing is cemented from 451' to the surface.

Plugging procedure will be to displace fluid in hole to mud laden fluid and equalize a 35 sack cement plug from 7480' to about 7290'. Recover as much 7" casing as practical. Equalize a 35 sack cement plug from 4713' to about 4610'. Cut off casing at surface if necessary and place 10 sack cement plug in top of casing. Weld a steel plate on top of 9-5/8" casing and install a steel marker at least 4" in diameter extending at least 4 feet above ground level. Mark the steel marker showing the following information:

Government 134#1 H-Sec 12-26S-24E

RECEIVED

JUN 24 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE OPERATIONS ENGINEER

DATE JUNE 22, 1976

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE