

DEPARTMENT OF THE INTERIOR (reverse side)
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		3. LEASE DESIGNATION AND SERIAL NO. L.C. 061716
2. NAME OF OPERATOR THE SUPERIOR OIL COMPANY		9. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 71 Conroe, TEXAS 77301		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) at surface 1980' FNL & 660' FEL of Section 12		8. FARM OR LEASE NAME Government "134"
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) RKB: 3879'		10. FIELD AND POOL, OR WILDCAT Washington Ranch
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12-26S-24E
		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. EVENTS PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 3-11-77 Displaced hole w/325 bbls 9.5# brine w/5250 lbs Zeogel.
- 3-14-77 Equalized 75 sx Class "A" cmt plug from 7089-7500'. (Plugging witnessed and approved by Mr. J. Brasfield of U.S.G.S. - Artesia, NM).
- 3-15-77 Ran 7" Jet cutter and cut 7" csg. @ 5700'. Pulled on csg. to 168,000#.
- 3-16-77 Worked 7" csg. loose w/290,000#. Pulled and laid down 79 jts of 7" 26# N-80 LT&C csg and 1 - 22' N-80 29# cut off. Filled hole w/9.5# mud laden brine.
- 3-18-77 Pulled and laid down 101 jts and 2 cut offs of 7" N-80 26# LT&C csg. Ran open ended csg to 5750'. Filled hole w/60 bbls 9.5# brine w/2250 lbs Zeogel. Equalized 50 sx. of El Toro reg. cmt from 5750' to 5579'. Pulled tbg to 4713' (9-5/8" shoe @ 4663'). Spotted 50 sx of Class "A" cmt from 4713' to 4567'. (Plugging witnessed and approved by Mr. B. Jones of U.S.G.S. - Artesia, NM).
- 3-19-77 Spotted 10 sx of El Toro Class "A" cmt from 32' to 4' below ground level. Cut top of csg @ 4' below ground level. Installed dry hole marker extending 5 1/2" above ground level.

210/GDM/11

18. I hereby certify that the foregoing is true and correct

SIGNED P. R. Blumenthal

TITLE Operations Engineer

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 31 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
DATE 3-28-77