

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

October 11, 1962

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation **Chinaberry Draw Unit** Well No. **1** in **12P**
(Company or Operator) (Unit)
SE 1/4 NW 1/4 of Sec. **3**, T. **25-S**, R. **26-E**, NMPM, **Wildcat** Pool
(40-acre Subdivision) **Eddy** County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 12,200'

It is proposed to plug and abandon as follows: Spot cement plugs at approximately:

- 12,100' to 12,200' - Bottom of well and across Miss.
- 11,650' to 11,750' - Across Barnett (11,720')
- 10,200' to 10,300' - Across Atoka (10,260')
- 9,000' to 9,100' - Cut off gas shows encountered 9,300' to 10,200'.
- 8,400' to 8,500' - Across 9-5/8" casing at 8446'.
- 7,900' to 8,000' - Across Window in 9-5/8" casing.
- 100' plug - Across 9-5/8" casing stub.
- 5,200' to 5,300' - If 9-5/8" stub is below 5300'.
- 1,750' to 1,850' - Across surface casing set at 1815' in top of Del.
- 350' to 400'
- 0' to 50' - Surface

Clean location and install marker. (Verbal permission obtained from Mr. Strenmetz with OCC in Artesia, N. M. and Mr. James Wright of the State Engineer Office, in Roswell, N. M., prior to beginning operations.)

Approved....., 19.....
Except as follows: **OCT 25 1962**

Gulf Oil Corporation

Company or Operator

By.....

Position **Area Production Manager**

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name **Gulf Oil Corporation**

Title.....

Address **Box 2167, Hobbs, New Mexico**

OIL AND GAS INSPECTOR