

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date April 23, 1958

The summary on this page is for the condition of the well at above date.

Commenced drilling ~~March 22~~-----, 19~~58~~ Finished drilling ~~March 31~~-----, 19~~58~~

(Denote gas by G)

IMPORTANT WATER SANDS

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

[illegible]

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8	231	175	Halliburton		
5-1/2	2175	150	Halliburton		

Heaving plug—Material Length Depth set

Adapters—Material Size

[illegible]

Rotary tools were used from surface feet to 2175 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

-----, 19. **58** Put to producing -----, 19. **58**
April 23 The production for the first 24 hours was ----- barrels of fluid of which ----- % was oil; ----- %
 emulsion; ----- % water; and ----- % sediment. **62** Gravity, °Bé. ----- **66**

If gas well, cu. ft. per 24 hours ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in. _____

_____, Driller _____, Driller
_____, Driller _____, Driller

FROM—	TO—	TOTAL FEET	FORMATION
0	225	225	Gypsum & Gravel
225	1345	1120	Anhydrite
1345	1533	188	Salt
1533	1625	92	Anhydrite
1625	1875	250	Salt
1875	2058	183	Anhydrite & lime
2058	2093	35	Black silty lime
2093	2175 TD	82	Sand, silty
			 SJ Tops: Top Delaware Lime - 2058 Top Delaware Sand - 2093

