

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

DUPLICATE

30-015-02516

Carlsbad, New Mexico, August 31, 1938

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading ILLEGIBLE noted above at the ILLEGIBLE Well No. ILLEGIBLE in the ILLEGIBLE County.

W. A. Snyder Pecos Irrigation Co. Company or Operator Lease

SE₂ of Sec. 15, T. 25 S., R. 28 East, N. M. P. M.,
Field, Eddy

The dates of this work were as follows: Completed August 31, 1938

Notice of intention to do the work was (~~xxxxx~~) submitted on Form C-102 on July 11, 1938
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Pounded gravel in hole from bottom to 2550 feet - Drove wooden plug in to top of 5 inch casing which was left in hole (2525- 2817) and cemented to well over top of five inch casing. Gas and water were all shut off by gravel and plug before cement was run. Filled with red clay mud to 1750 ft. - 5 sacks cement - top of salt. Pulled all 8 inch casing. Cavings filled hole to 1350 feet where cement plug was set. Filled with red clay mud to 650 ft. Cement plug for bottom of top salt. Filled with red clay mud to 300 ft. - cement plug set for top of salt. Shot off 10 inch casing at 120 ft. Left 35 ft. of 10" casing in hole. Filled with red clay mud to 100 feet. Cemented thru surface water sand to 75 feet. Filled with red clay mud to 12 ft where 16 feet joint of 4" casing was cemented with 5 sacks cement. 4" casing cemented at surface also.

Witnessed by H. Miller W. A. Snyder Secretary
Name Operator Title

Subscribed and sworn to before me this 7th
day of September, 1938

Jessie Douglas
Notary Public

My Commission expires February 28, 1940

I hereby swear or affirm that the information given above is true and correct.

Name H. Miller
Position Foreman in Charge

Representing W. A. Snyder
Company or Operator

Address Carlsbad New Mexico

Remarks:

Wes Walker
Name

Oil & Gas Inspector

Title

[illegible]