

0									

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Aldridge & Stroud, Inc. **Signal-Pecos Irrigation Company**
(Company or Operator) (Lease)

Well No. 1, in 10 $\frac{1}{4}$ of 30 $\frac{1}{4}$ of Sec. 30, T. 25 S, R. 28 E, NMPM.

Wildcat Pool, Edley County.

Well is 560 feet from North line and 560 feet from West line of Section 30. If State Land the Oil and Gas Lease No. is _____

Drilling Commenced June 9, 1956 Drilling was Completed July 22, 1956

Name of Drilling Contractor Aldridge & Stroud, Inc.

Address P. O. Box 982, Odessa, Texas

Elevation above sea level at Top of Tubing Head 2999' Ground Level The information given is to be kept confidential until Not Confidential, 19____

OIL SANDS OR ZONES

No. 1, from 2299' to 2309' Rainbow No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 757' to 760' feet. 1/2 bailer water per hr.

No. 2, from 2225' to 2240' feet. 30 gallons water per hr.

No. 3, from 2299' to 2320' feet. 75 gallons water per hr.

No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4"	32	New	340'	Barkin	340'		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Cement plug from TD 2320' to 2275'

Filled w/mud to 1400'

5 sack cement plug 1400'

Filled w/mud to 900'

5 sack cement plug 900'

Filled w/mud to 500'

5 sack cement plug 500'

Result of Production Stimulation Filled w/mud to 10'

5 sack cement plug from 10' to bottom of cellar

Depth Cleaned Out _____

1 ORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
 Cable tools were used from surface feet to 2320' TD feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing Dry Abandoned July 4, 1956

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
 was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
 Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
 liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	6 T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	5	5	Cellar	1445	1460	15	Shale
5	15	10	Caliche	1460	1468	8	Anhydrite
15	40	25	Sand & gy	1468	1483	17	Blue shale
40	85	45	Sand & gravel	1483	1630	147	Anhydrite
85	260	175	Lime	1630	1670	40	Anhydrite & shale
260	267	7	Red shale	1670	1085	395	Anhydrite
267	278	11	Lime & gy	1085	1090	25	Lime
278	285	7	Red Bed	1090	1115	25	Anhydrite
285	293	8	Anhydrite	1115	1135	20	Brown lime
293	300	7	Red Rock	1135	1155	20	Lime
300	334	34	Anhydrite	1155	1185	30	Anhydrite
334	338	4	Blue shale	1185	1210	25	Brown lime
338	348	10	Anhydrite	1210	1235	25	Lime
348	357	9	Blue shale	1235	1345	110	Anhydrite
357	365	8	Anhydrite	1345	1415	70	Anhydrite lime
365	395	30	Shale	1415	1485	70	Lime
395	415	20	Anhydrite	1485	1630	145	Salt
415	420	5	Shale	1630	1722	92	Lime
420	438	18	Anhydrite & shale	1722	2050	328	Salt
438	446	8	Anhydrite	2050	2290	240	Lime
				2290	2320	30	Sand
				2320	T.D.		

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Aldridge & Stroud, Inc.
 Name W. E. Stroud, Jr.

Address P.O. Box 952, Odessa, Texas
 Position or Title Secretary Treasurer

(Date)