

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. **LC 061981**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

30-015-03735

April 14, 1958

Well No. **1-Boothe** is located **660** ft. from **[N]** line and **660** ft. from **[E]** line of sec. **14**
NW 1/4 14 **T6S 29E** **R14W**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilco **INDY** **N. M.**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **N.A.** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)


Plugged with cement by Halliburton and mudded.
 Proper monument erected and marked, as follows:
 Halliburton plug and cement at from TD to 3055' - 10 sxs of cement. . . Second plug set at 1650' - 10 sxs of cement. . . Set Halliburton plug at 1650' with 10 sxs of cement and mudded to bottom. . . Set top plug at 325' with 25 sxs of cement and mudded to top and proper cement and marker set.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **FORD CHAPMAN**

Address **BOX 1512**

PECOS, TEXAS

By 
 Title **OWNER**