Form 9-381 a (Feb. 1951)		M. M. O. C. C. CERC	Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
	(8	UBMIT IN TRIPLICATE)	Land Office N.M.
		UNITED STATES	Losan gen UL5353
	DEPART	MENT OF THE INTERIOR	R / Unit
	1000	EOLOGICAL SURVEY	1 ONTOT WE
	1	and the later of the second	Same Sight
SUN		er #1 Continental-Federal ES AND REPORTS (THAT
			D. C. C.
NOTICE OF INTENTION T	O DRILL	SUBSEQUENT REPORT OF W	ATER SHUT-OFF
	O CHANGE PLANS		OOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF			TERING CASING
r -	O RE-DRILL OR REPAIR WELL		-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE			
	O ABANDON WELL	SUFFLEMENTART WELL HIST	'ORY
	(INDICATE ABOVE BY CHE	CK MARK NATURE OF REPORT, NOTICE, OR O	THER DATA)
		ti October	20, 1958 19
a de la construcción de la const	Juni darite	ale Tot Part	, 17
Vell No. 1	is located 660 ft	t. from Ny line and 660 ft	$\operatorname{from}\left(\overset{E}{\swarrow} \right)$ line of sec. <u>17</u>
NE/4 NE/4 Sec.		S. 31 E. N.M.P.M. (Range) (Meridian	
Wildcat	Ec	ldy County	New Mexico
(Field)	(County or Subdivision)	(State or Territory)
he elevation of th	e derrick floor above	sea level is <u>3550</u> ft.	
	Γ	DETAILS OF WORK	
State names of and expect	ed depths to objective sands; ing points, i	show sizes, weights, and lengths of propose and all other important proposed work)	d casings; indicate mudding jobs, cement-
as per teleph		n Frost, USGS, Artesia, 1 of October 15, 1958, thi Collowing manner:	
Laugora ana a			
	cement at T. D. L	15051.	
Set 20 sacks	cement at T. D. L cement at top of		
Set 20 sacks Set 20 sacks		black lime at 4403'.	ter a second
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks	cement at top of cement at base of cement at top of	black lime at 4403'. Salt at 4170'.	The second D
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Fulled 8-5/8"	cement at top of cement at base of cement at top of casing.	black lime at 4403'. 'salt at 4170'. salt at 1300'.	
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks	cement at top of cement at base of cement at top of casing. cement at bottom	black lime at 4403'. salt at 4170'. salt at 1300'. of 13 3/8" casing at 250	
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks	cement at top of cement at base of cement at top of casing. cement at bottom cement at surface	black lime at 4403'. 'salt at 4170'. salt at 1300'. of 13 3/8" casing at 250	
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks	cement at top of cement at base of cement at top of casing. cement at bottom	black lime at 4403'. 'salt at 4170'. salt at 1300'. of 13 3/8" casing at 250	D. 201 2 ? 1958
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks Placed regulat	cement at top of cement at base of cement at top of casing. cement at bottom cement at surface ion marker at sur	black lime at 4403'. Salt at 4170'. salt at 1300'. of 13 3/8" casing at 250 face. Frace.	pt. 1958 Store operations may be commenced.
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks Placed regulat Lunderstand that this Company	cement at top of cement at base of cement at top of casing. cement at bottom cement at surface ion marker at sur plan of work must receive app J. Weaver	black lime at 4403'. Salt at 4170'. salt at 1300'. of 13 3/8" casing at 250 face. roval in writing by the Geological Survey b	pt. 1958 Store operations may be commenced.
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks Placed regulat I understand that this Company W. Address 131	cement at top of cement at base of cement at top of casing. cement at bottom cement at surface ion marker at sur	black lime at 4403'. Salt at 4170'. salt at 1300'. of 13 3/8" casing at 250 face. roval in writing by the Geological Survey b conal Bank Bldg.	pt. 1958 Store operations may be commenced.
Set 20 sacks Set 20 sacks Set 20 sacks Set 20 sacks Pulled 8-5/8" Set 20 sacks Set 10 sacks Placed regulat Lunderstand that this Company W. 131	cement at top of cement at base of cement at top of casing. cement at bottom cement at surface ion marker at sur plan of work must receive app J. Weaver O Fort Worth Nati	black lime at 4403'. Salt at 4170'. salt at 1300'. of 13 3/8" casing at 250 face. roval in writing by the Geological Survey b onal Bank Bldg. By /s/	pt. 1958 Store operations may be commenced.

GPO 862040