

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT  
(Other in  
verse side)

TR  
ct)

CATE\*  
on re

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

RECEIVED BY

JAN 2 1985 SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ GAS ☐  
ARTESIAN OFFICE ☐ OTHER ☐

2. NAME OF OPERATOR  
HANSON OPERATING COMPANY, INC. ✓

3. ADDRESS OF OPERATOR

P. O. BOX #1515, ROSWELL, NEW MEXICO 88202-1515

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

330' FSL & 2310' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3145' GR

5. LEASE DESIGNATION AND SERIAL NO.

LC 068282-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

HANSON FEDERAL

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Brushy Canyon Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 25, T. 26S, R. 31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☒

(Other) Cementing

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

☒

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Found top of cement @ 5400'.

Perforate @ 5320' to squeeze cement to 200' above base of salt.

Cement w/500 sx Class "C" neat foam & 200 sx Class "C" 2% Ca Cl.

Ran temperature survey 12 hrs later. Found top of cement @ 3520'.

Pressure tested casing to 1000# - no pressure decrease.

First run w/perf gun - shot 8322', 21', 18', 13', 10', 08', 01', 8297', 94', 89' & 84'.

Second run w/perf gun - shot 8277', 71', 69', 63' & 61'.

Acidized w/2000 gal 15% NEFE.

18. I hereby certify that the foregoing is true and correct

SIGNED

Brenda R. Kitt

TITLE

Production Analyst

DATE

12/27/84

(This space for Federal or State Office Use)

APPROVED BY

DEC 3 1984

TITLE

DATE

Carlsbad, NEW MEXICO

\*See Instructions on Reverse Side