

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

The summary on this page is for the condition of the well at above date.

Commenced drilling 5-23-, 1955 Finished drilling 6-18, 1955

(Denote gas by G)

Well drilled with rotary and no water sands tested.

CASING RECORD

MUDDING AND CEMENTING RECORD

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

TOOLS USED

Rotary tools were used from 0 feet to 4138 feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

_____, 19____ Put to producing 6-18-____, 1955

The production for the first 24 hours was 162 barrels of fluid of which 78.3% was oil; -----% emulsion; 21.7% water; and -----% sediment. Gravity, °Bé. 41.4

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

H. V. Gray	Driller	E. L. Craig	Driller
W. E. Kimbrell	Driller	Ed. ...	Driller

FORMATION RECORD

FROM--	TO--	TOTAL FEET	FORMATION
0	75	75	Caliche, Sand & Gravel
75	452	377	Gravel, Sand & Shale
452	699	247	Red Beds
699	876	177	Shale & Shells
876	915	39	Anhy
915	1465	550	Anhy, Gyp, Sand & Shale
1465	1990	525	Anhy, Gyp & Shale
1990	2109	119	Anhy, Salt stringers
2109	2894	785	Anhy, & Gyp
2894	3081	187	Anhy, Gyp & Salt Stringers
3081	3373	292	Anhy
3373	3516	143	Salt
3516	3616	100	Anhy
3616	3864	248	Salt
3864	4064	200	Anhy
4064	4095	31	Black Lime
4095	4122	27	Black Lime & Sand
4122	4138	16	Sandy Lime
	4138		Total Depth

FORMATION RECORD--Continued

TO-	TOTAL FEET	FORMATION
		Deviation Record
		160'-1/4°
		320'-1/4°
		640'-1°
		800'-2°
		900'-1-3/4°
		1050'-2 1/2°
		1210'-2°
		1360'-2 1/2°
		1530'-2-3/4°
		1600'-2 1/2°
		1750'-2°
		1908'-2°
		1961'-1-3/4°
		2100'-2°
		2240'-1-3/4°
		2430'-2-3/4°
		2551'-2 1/2°
		2710'-1-3/4°
		2850'-1/2°
		2950'-1/2°
		3080'-1/2°
		3237'-3/4°
		3390'-1/2°
		3550'-1°
		3700'-1 1/2°
		3860'-2°
		3990'-2°

HISTORY OF OIL OR GAS WELL

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing. Well was drilled to a total depth of 4138' and 5 1/2" casing was set at 4112' with 400 sacks cement. Open hole from 4112' to 4138' sand-frac with 2000 gallons gel lease crude with 1 lb of sand per gallon and well swabbed until load oil recovered. Well shut-in for 12 hrs while rotary was moved off. On test flowed 54 bbls of oil and 15 bbls of water in 8 hours through 1/2" choke. GOR is 433.